

TP-Link Archer C54 AC1200 Dual-Band Wi-Fi router



1167Mb/s, IEEE 802.11a/b/g/n/ac (Wi-Fi 5), WAN (100Mb/s): 1 port, LAN (100Mb/s): 4 port, antennák száma: 4db, fekete

Cikkszám: ARCHER C54

Ár:

15 940 Ft

Garancia: 3 Év

Standards	Wi-Fi 5
	IEEE 802.11ac/n/a 5 GHz
	IEEE 802.11n/b/g 2.4 GHz
WiFi Speeds	AC1200
	5 GHz: 867 Mbps (802.11ac)
	2.4 GHz: 300 Mbps (802.11n)
	3 Bedroom Houses

WiFi Range	4× Fixed Antennas
	Multiple antennas form a signal-boosting array to cover more directions and large areas
	Beamforming
	Concentrates wireless signal strength towards clients to expand WiFi range
	Medium

WiFi Capacity	Dual-Band
	Allocate devices to different bands for optimal performance

Working Modes	MU-MIMO
	Simultaneously communicates with multiple MU-MIMO clients
	Router Mode
	Access Point Mode
	Range Extender Mode

HARDWARE	
Processor	Single-Core CPU
Ethernet Ports	1× 10/100 Mbps WAN Port
	4× 10/100 Mbps LAN Ports
Buttons	WPS/Reset Button
Power	9 V ? 0.85 A

BIZTONSÁG	WEP
	WPA
	WPA2
WiFi Encryption	WPA/WPA2-Enterprise (802.1x)
	SPI Firewall
	Access Control
Network Security	IP & MAC Binding

Guest Network	Application Layer Gateway
	1× 5 GHz Guest Network
	1× 2.4 GHz Guest Network
SOFTWARE	
Protocols	IPv4
	IPv6
Parental Controls	URL Filtering
	Time Controls
	Dynamic IP
WAN Types	Static IP
	PPPoE
	PPTP
	L2TP
Quality of Service	QoS by Device
	Port Forwarding
NAT Forwarding	Port Triggering
	DMZ
	UPnP
	IGMP Proxy
IPTV	IGMP Snooping
	Bridge
	Tag VLAN
DHCP	Address Reservation
	DHCP Client List
	Server
DDNS	TP-Link
	NO-IP
	DynDNS
Management	Tether App
	Webpage
Check Web Emulator>	
PHYSICAL	
Dimensions (W×D×H)	4.5 × 4.2 × 1.0 in
	(115 × 106.7 × 24.3 mm)
Package Contents	Wi-Fi Router Archer C54
	Power Adapter
	RJ45 Ethernet Cable
	Quick Installation Guide
OTHER	
System Requirements	Internet Explorer 11+, Firefox 12.0+, Chrome 20.0+, Safari 4.0+, or other JavaScript-enabled browser
	Cable or DSL Modem (if needed)
Certifications	Subscription with an internet service provider (for internet access)
	FCC, CE, RoHS
Environment	Operating Temperature: 0?~40? (32? ~104?)
	Storage Temperature: -40?~60? (-40? ~140?)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing
TEST DATA	
WiFi Transmission Power	CE EIRP:
	<20dBm(2.4GHz)
	<23dBm(5GHz)
	FCC:
	<30dBm(2.4GHz & 5GHz)
	5GHz:
WiFi Reception Sensitivity	11a 6Mbps:-93dBm;11a 54Mbps:-78dBm;
	11ac HT20 mcs8:69dBm;11ac HT40 mcs9:-65dBm;
	11ac HT80 mcs9:-62dBm;
	2.4GHz:

11g 54Mbps:-78dBm;
11n HT20 mcs7:-74dBm;
11n HT40 mcs7:-71dbm;

Dual-Band	Van
LAN (100Mb/s)	4
WAN (100Mb/s)	1
Wi-Fi átviteli sebesség	1167
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac (Wi-Fi 5)
Wi-Fi titkosítás	WEP;WPA2;WPA2-Enterprise
Gyártó	TP-Link
antenna típusa	külső fix
antennák száma	4
WI-FI	Van
szín	fekete