Szanex Bt.

Cégjegyzék szám: 05-06-005646 Adószám: 21302541-2-05 3700 Kazincbarcika, Dózsa Gy. út 24. szanex@szanex.hu (48) 512-880

StarTech Triple-Monitor USB3.0 dokkoló

20 M2 ...

illesztés: USB3.0, DisplayPort kimenet: 2db, HDMI kimenet: 1db, 1Gb/s,

fejhallgató kimenet, mikrofon bemenet

Cikkszám: USB3DOCKH2DP

Ár:

84 930 Ft

This triple-video docking station for laptops merges cutting-edge technology and high-quality hardware with innovative design elements. It's one of the first universal laptop docking stations to support three external displays.

When coupled with your laptop display, the docking station makes it easy to create a high-performance, high-resolution workstation with four displays in total, including one 4K DisplayPortTM display.

With its expanded display presence, this specialty docking station is ideal for a wide range of applications. It offers a fast and easy way to maximize your laptop's workable screen space, which is perfect for graphic and web designers, animators, financial analysts and more.

A four-display workstation helps you get more done

The triple-video docking station uniquely integrates two video chipsets, making it possible to connect one HDMI® and two DisplayPort monitors to your laptop. With four total displays, you can manage several programs at once and avoid the nuisance of minimizing or rearranging windows. Plus it delivers 4K cinema resolution to the first DisplayPort monitor.

This versatile docking station boosts your workflow with minimal impact on your budget, and it connects to your laptop or Windows based tablet through just one USB 3.0 (also known as USB 3.1 Gen 1 - 5Gbps) cable.

4K Ultra HD delivers ultimate display potential

Why sacrifice image quality for display quantity? This top-of-the-line docking station offers the best of both worlds. It features three video ports, including a DisplayPort connection that supports $4K \times 2K$ (3840 $\times 2160p$ - 30Hz) Ultra HD resolution.

The docking station offers an enhanced method of upgrading the display capabilities of your computer. While many laptop docks offer two video outputs, they often don't support three external displays, or Ultra High Definition.

The full-featured dock delivers crystal-clear image quality without sacrificing the total number of external monitor connections, which is ideal for highly detailed and graphically intense applications.

Plenty of ports gives you everything you need

This triple-video docking station lets you connect up to 12 peripherals, to transform your laptop into a powerful, full-sized workstation.

The dock also makes it easy to quickly charge your mobile devices, using the always-on fast-charge port. Plus, with five USB 3.0 ports, a headset jack, separate 3.5mm audio and microphone ports, as well as an RJ45 Gigabit Ethernet port, you have all the connections you need with no complications or extra costs.

Unlike some docks, this easy-to-use docking station offers seamless, error-free driver installation that will have you up and running fast.

The USB3DOCKH2DP is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Maximum Supported Resolutions*

Video Output Configuration	Max DisplayPort Resolution (Video 1)	Max HDMI Resolution (Video 2)	Max DisplayPort Resolution (Video 3)
DisplayPort 1 (Single Display)	3840 x 2160p (4K)	N/A	N/A
DisplayPort 2 (Single Display)	N/A	N/A	2560 x 1600p
HDMI (Single Display)	N/A	2560 x 1440p	N/A
DisplayPort 1 and HDMI (Two Displays)	3840 x 2160p (4K)	2560 x 1440p	N/A
DisplayPort 2 and HDMI (Two Displays)	N/A	2048 x 1152p	2048 x 1152p
DisplayPort 1 and DisplayPort 2 (Two Displays)	3840 x 2160p (4K)	N/A	2560 x 1600p
DisplayPort 1, DisplayPort 2, HDMI (Three Displays)	3840 x 2160p (4K)	2048 x 1152p	2048 x 1152p

^{*}Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

Hardware

4K Support Yes Bus Type **USB 3.0**

Chipset ID DisplayLink - DL-5910 (Display, LAN, Audio)

VLI - VL812 (USB 3.0 w/ Charge)

Displays Supported Fast-Charge Port(s) Yes

Industry Standards USB Battery Charging Specification Rev. 1.2

IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

USB 3.0 - Backward compatible with USB 2.0/1.1

Performance

Auto MDIX Yes

Compatible Networks 10/100/1000 Mbps

Full Duplex Support Yes

Maximum Data 5 Gbps (USB 3.0)

Transfer Rate 2 Gbps (Ethernet; Full-Duplex)

Maximum Digital 3840 x 2160 @ 30Hz (DisplayPort Video 1 - Single Display)

Resolutions

2560 x 1600 (DisplayPort Video 3 - Single Display)

2560 x 1440 (HDMI - Single Display)

Lower resolutions are also supported. For example, if the max is 3840 x 2160p (4K), it also supports 2560 x 1600p and 2560 x 1440p.

Please see the manual for supported resolutions when using different combinations of displays (up to three external displays).

Type and Rate

USB 3.0 - 5 Gbit/s

Yes

UASP Support Connector(s)

Connector Type(s) 2 - DisplayPort (20 pin) Female

1 - HDMI (19 pin) Female

1 - USB 3.0 A (Fast-Charge; 9 pin; SuperSpeed) Female

4 - USB Type-A (9 pin) USB 3.0 Female

1 - RJ-45 Female

1 - 3.5 mm Mini-Jack (4 Position) Female 2 - 3.5 mm Mini-Jack (3 Position) Female 1 - USB Type-B (9 pin) USB 3.0 Female

1 - Security Lock Slot Female

Software

OS Compatibility Windows ® 10 (32-bit or 64-bit), 8 / 8.1 (32-bit or 64-bit), 7 (32-bit or 64-bit)

Mac OS® 10.8 and later (tested up to 10.11)

Special Notes / Requirements

Note 4K resolution is supported on the DisplayPort Video 1 port only. A 4K-capable DisplayPort

display is required to achieve 4Kx2K resolutions

If connected to a USB 2.0 host port, or if using a USB 2.0 host connection cable,

performance may be limited (USB 3.0 host cable included)

USB 3.0 is also known as USB 3.1 Gen 1; this connectivity standard offers speeds up to

5Gbps

System and Cable

Requirements

USB-enabled computer with an available USB 3.0 port

Indicators

LED Indicators

1 - Link (Green) 1 - Activity (Amber)

Power

Center Tip Polarity Positive Input Current 1.5 A

Input Voltage 100 ~ 240 AC

Output Current 6.5 A
Output Voltage 5 DC
Plug Type N

Power Consumption 32.5 W Max

Power Source AC Adapter Included

Environmental

Humidity 0~90% RH

Operating 0°C to 40°C (32°F to 104°F)

Temperature

Storage Temperature -10°C to 80°C (14°F to 176°F)

Physical Characteristics

Color Black & Silver

Enclosure Type Plastic

Product Height 1.3 in [34 mm]
Product Length 10.6 in [270 mm]
Product Weight 13.3 oz [378 g]
Product Width 3.2 in [82 mm]

Packaging Information

Shipping (Package) 38.3 oz [1085 g]

Weight

What's in the Box

Included in Package 1 - triple-video laptop docking station

1 - USB 3.0 host cable

1 - universal power adapter (NA/EU/UK/AU)

1 - instruction manual