

TP-Link TL-SL1311MP PoE switch

LAN (100Mb/s): 8 port, LAN (1Gb/s): 2 port, SFP: 1db, energiafelhasználás: 124W, szürke

Cikkszám: TL-SL1311MP

Ár:

47 880 Ft



Garancia: 5 Év

Interface

- 8× 10/100 Mbps 802.3af/at PoE+ Ports, 2× Gigabit RJ45 Ports, 1× Gigabit SFP Port
- AUTO Negotiation
- AUTO MDI/MDIX
- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)

Network Media

Fan Quantity

Fanless

Physical Security Lock

Yes

External Power Supply

External Power Adapter (Output: 53.5VDC / 2.43A)

Packet Forwarding Rate

5.6544 Mpps

PoE Ports (RJ45)

- Standard: 802.3 af/at compliant
- PoE Ports: Ports 1-8
- Power Supply: 124 W

Mac Address Table

2K

Jumbo Frame

16 KB

Switching Capacity

7.6 Gbps

Dimensions (W x D x H)

8.2 × 4.9 × 1.0 in (209 × 126 × 26 mm)

Max Power Consumption

- 5.95 W (220/50 Hz. no PD connected)
- 140.92 W (220/50 Hz. with 124 W PD connected)
- 20.29 BTU/h (no PD connected)

Max Heat Dissipation

- 480.54 BTU/h (220/50 Hz. with 124 W PD connected)

SOFTWARE FEATURES

Transmission Method

Store-And-Forward

Advanced Functions

- Compatible With IEEE 802.3af/at Compliant PDs
- Extend Mode Button (Ports 1-4 and Ports 1-8, Up to 250 m PoE power supply and data transmission)
- Isolation Mode Button (Ports 1-8)
- PoE Auto Recovery Button (Ports 1-8)
- Mac Address Auto-Learning and Auto-Aging
- IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure for Half-Duplex Mode

OTHERS

Certification

- FCC, CE, RoHS
- TL-SL1311MP

Package Contents

- Power Adapter
- Installation Guide
- Operating Temperature: 0-40 ° (32-104 °)
- Storage Temperature: -40-70 ° (-40-158 °)

Environment

Environment

- Operating Humidity: 10-90% RH non-condensing
- Storage Humidity: 5-90% RH non-condensing

energiafelhasználás	124
LAN (100Mb/s)	8
LAN (1Gb/s)	2
PoE port	8
SFP	1
Gyártó	TP-Link
PoE	Van
szín	szürke