

TP-Link ER7206 SafeStream VPN router

WAN (1Gb/s): 3 port, LAN (1Gb/s): 4 port, SFP: 1db, menedzselhető, VPN csatornák száma: 100db, tűzfal, szűrke

Cikkszám: ER7206

Ár:
106 680 Ft



Garancia: 5 Év

Standards and
Protocols

- IEEE 802.3, IEEE802.3u, IEEE802.3ab, IEEE 802.3z, IEEE 802.3x, IEEE 802.1q
- TCP/IP, DHCP, ICMP, NAT, PPPoE, NTP, HTTP, HTTPS, DNS, IPSec, PPTP, L2TP, OpenVPN, SNMP

Interface

- 1 Fixed Gigabit SFP WAN Port
- 1 Fixed Gigabit RJ45 WAN Port
- 2 Fixed Gigabit RJ45 LAN Ports
- 2 Changeable Gigabit RJ45 WAN/LAN Ports
- 10BASE-T: UTP category 3, 4, 5 cable (Max 100m)

Network Media

- EIA/TIA-568 100Ω STP (Max 100m)
- 100BASE-TX: UTP category 5, 5e cable (Max 100m)
- EIA/TIA-568 100Ω STP (Max 100m)
- 1000BASE-T: UTP category 5, 5e, 6 cable (Max 100m)

Button

Reset Button

Power Supply

100-240 V~50/60 Hz

Flash

SPI 4MB + NAND 128MB

DRAM

512MB

LED

PWR, SYS, SFP WAN, WAN (Speed, Link/Act), LAN (Speed, Link/Act)

Dimensions (W x D x
H)

8.9 × 5.2 × 1.4 in.
(226 × 131 × 35 mm)

PERFORMANCE

Concurrent Session 150,000

IPsec VPN Throughput291.6 Mbps

BASIC FUNCTIONS

- Static/Dynamic IP
- PPPoE
- PPTP
- L2TP

WAN Connection Type

MAC Clone

Modify WAN/LAN MAC Address[†]

DHCP

- DHCP Server
- DHCP Address Reservation
- Multi-IP Interfaces*
- Multi-Net DHCP*

VLAN

802.1Q VLAN

IPTV

IGMP v2/v3 Proxy

ADVANCED FUNCTIONS

ACL IP/Port/Protocol/Domain Name Filtering

Advanced Routing

- Static Routing
- Policy Routing

Bandwidth Control

- IP/Port-based Bandwidth Control

Bandwidth Control	• Guarantee & Limited Bandwidth • Intelligent Load Balance
Load Balance	• Application Optimized Routing • Link Backup (Timing[§], Failover) • Online Detection • One-to-One NAT[§] • Multi-Net NAT
NAT	• Virtual Server • Port Triggering[§] • NAT-DMZ • FTP/H.323/SIP/IPSec/PPTP ALG, UPnP • SPI Firewall • VPN Passthrough
Security	• FTP/H.323/PPTP/SIP/IPsec ALG • DoS Defence, Ping of Death • Local Management
Session Limit	IP-based Session Limit
VPN	• 100 IPSec VPN Tunnels • LAN-to-LAN, Client-to-LAN • Main, Aggressive Negotiation Mode • DES, 3DES, AES128, AES192, AES256 Encryption Algorithm
IPsec VPN	• IKEv1/v2* • MD5, SHA1 Authentication Algorithm • NAT Traversal (NAT-T) • Dead Peer Detection (DPD) • Perfect Forward Secrecy (PFS) • PPTP VPN Server
PPTP VPN	• 10 PPTP VPN Clients • 50 Tunnels • PPTP with MPPE Encryption • L2TP VPN Server
L2TP VPN	• 10 L2TP VPN Clients • 50 Tunnels • L2TP over IPSec • OpenVPN Server*
OpenVPN	• 10 OpenVPN Clients* • 50 OpenVPN Tunnels*
SECURITY	
Filtering	WEB Group Filtering [§] URL Filtering Web Security [§] • Sending GARP Packets[§]
ARP Inspection	• ARP Scanning[§] • IP-MAC Binding[§] • TCP/UDP/ICMP Flood Defense
Attack Defense	• Block TCP Scan (Stealth FIN/Xmas/Null) • Block Ping from WAN
Access Control	Source/Destination IP Based Access Control
AUTHENTICATION	
Web Authentication	• No Authentication • Simple Password* • Hotspot(Local User / Voucher* / SMS* / Radius*) • External Radius Sever • External Portal Sever* • Facebook*
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Cloud-Based Controller • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller

Cloud Access	Yes (Through OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller)
Service	Dynamic DNS (Dyndns, No-IP, Peanuthull, Comexe) • Web Management Interface • Remote Management • Export & Import Configuration
Maintenance	• SNMP v1/v2c/v3* • Diagnostics (Ping & Traceroute)[§] • NTP Synchronize[§] • Syslog Support • Automatic Device Discovery • Intelligent Network Monitoring • Abnormal Event Warnings
Management Features	• Unified Configuration • Reboot Schedule • Captive Portal Configuration • ZTP (Zero-Touch Provisioning)**
OTHERS	
Certification	CE, FCC, RoHS • ER7206
Package Contents	• Power Cord • Quick Installation Guide
Environment	• Operating Temperature: 0–40 ℃ (32–104 ℉); • Storage Temperature: -40–70 ℃ (-40–158 ℉) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Dual-personality Ethernet port	2
LAN (1Gb/s)	4
SFP	1
VPN csatornák száma	100
WAN (1Gb/s)	3
Gyártó	TP-Link
menedzselhető	Van
tűzfal	Van
szín	szürke