

TP-Link TL-SG1210MPE Easy Smart PoE switch

LAN (1Gb/s): 10 port, SFP: 1db, menedzselhető, energiafelhasználás: 123W, szürke

Cikkszám: TL-SG1210MPE

Ár:

69 340 Ft



Garancia: 5 Év

Standards and Protocols

IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p, IEEE 802.3at, IEEE 802.3z
9× 10/100/1000 Mbps RJ45 Ports

Interface

1× 1000 Mbps Combo SFP/RJ45 Port

AUTO Negotiation/AUTO MDI/MDIX

10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

EIA/TIA-568 100Ω STP (maximum 100m)

Network Media

100BASE-TX: UTP category 5, 5e cable (maximum 100m)

EIA/TIA-568 100Ω STP (maximum 100m)

1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)

EIA/TIA-568 100Ω STP (maximum 100m)

Fan Quantity

Fanless

Power Supply

External Power Adapter (Output: 53.5 VDC/2.43 A)

Standard: 802.3 af/at compliant

PoE Ports (RJ45)

PoE Ports: Port 1- Port 8

PoE Power Budget: 123 W

Dimensions (W x D x H)

8.2 × 4.9 × 1.0 in (209 × 126 × 26 mm)

Max Power Consumption

7.66 W (220V / 50Hz with no PD connected)

141.54 W (220V / 50Hz with 123 W PD connected)

Max Heat Dissipation

26.12 BTU/h (220V / 50Hz with no PD connected)

482.65 BTU/h (220V / 50Hz with 123 W PD connected)

PERFORMANCE

Switching Capacity

20 Gbps

Packet Forwarding Rate

14.88 Mpps

MAC Address Table

4 K

Jumbo Frame

16 KB

SOFTWARE FEATURES

Support Port-Based/802.1p/DSCP priority

Quality of Service

Support 4 priority queues

Rate Limit

Storm Control

IGMP Snooping V1/V2/V3

Static Link Aggregation

L2 Features

Port Mirroring

Cable Diagnostics

Loop Prevention

VLAN

Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs)

MTU/Port/Tag VLAN

PoE

Extend Mode**

PoE	PoE Auto Recovery
Management	Web-based GUI
	Easy Smart Configuration Utility
Transmission Method	Store-And-Forward
OTHERS	
Certification	FCC, CE, RoHS
	TL-SG1210MPE
Package Contents	Power Adapter
	Installation Guide
	Rubber Feet
System Requirements	Microsoft® Windows® for running Utility
	Operating Temperature: 0?~40? (32?~104?)
Environment	Storage Temperature: -40?~70? (-40?~158?)
	Operating Humidity: 10%~90%RH non-condensing
	Storage Humidity: 5%~95%RH non-condensing

Dual-personality Ethernet port	1
energiafelhasználás	123
LAN (1Gb/s)	10
PoE port	8
SFP	1
Gyártó	TP-Link
menedzselhető	Van
PoE	Van
szín	szürke