

StarTech Gigabit Ethernet to SFP Ethernet media konverter

LAN (1Gb/s): 1 port, SFP: 1db

Cikkszám: MCM1110SFP

Ár:

38 470 Ft



This fiber media converter offers an easy, cost-effective way to extend your network over fiber, using the SFP of your choice. It converts a copper RJ45 Ethernet connection to Gigabit fiber to extend your network over longer distances or connect workstations to switches. The converter provides a powerful networking solution for campuses, businesses, government facilities, stadiums, or other areas requiring network access.

A cost-effective extension and flexible performance

The Gigabit fiber media converter provides a cost-efficient way to connect your Ethernet network to remote devices over a fiber backbone. It features an open SFP slot that lets you choose the MSA-compliant Gigabit SFP that best suits your fiber connection mode (single / multimode) and distance requirements.

A versatile way to connect different networks

Fully compatible with 10/100/1000Base-T Ethernet networks, the fiber media converter supports auto negotiation to bridge different speed networks and devices to a Gigabit fiber network. It provides versatile connectivity to your existing networks and devices, allowing you to maximize the usage and performance of legacy equipment.

Installation is fast and easy

The unmanaged fiber media converter has a standalone design with simple plug-and-play set-up to ensure fast and easy installation. Compact in size, the converter gives you flexible installation options - including a wall mounting option.

The MCM1110SFP is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Hardware

Industry Standards	IEEE 802.3 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3z 1000BASE-SX
	IEEE 802.3z 1000BASE-LX

PoE No

WDM No

Performance

Auto MDIX	Yes
Compatible Networks	10/100/1000 Mbps
Fiber Operating Mode	Full-Duplex
Fiber Type	Multi Mode
	Single Mode
Maximum Data Transfer Rate	1 Gbps
MTBF	> 50,000 hours at 25°C

Connector(s)

- Local Unit Connectors 1 - RJ-45 Female
- 1 - SFP Slot Female

Special Notes / Requirements

Note Fiber data transfer speeds and distances are dependent on the SFP transceiver used (sold separately)

Indicators

- LED Indicators 1 - Power
- 1 - Fiber Port Link/Act
- 1 - Copper Port Link/Act
- 1 - 1000 Mbps

Power

- Center Tip Polarity Positive
- Input Current 1 A
- Input Voltage 100 ~ 240 AC
- Output Current 2 A
- Output Voltage 5 DC
- Plug Type N
- Power Consumption 5 W Max
- Power Source AC Adapter Included

Environmental

- Humidity 5~95% RH (Non-condensing)
- Operating Temperature 0°C to 50°C (32°F to 122°F)
- Storage Temperature -10°C to 70°C (14°F to 158°F)

Physical Characteristics

- Color Brown
- Enclosure Type Steel
- Product Height 1 in [26 mm]
- Product Length 3.7 in [95 mm]
- Product Weight 6.5 oz [185 g]
- Product Width 2.8 in [70 mm]

Packaging Information

- Shipping (Package) 17.3 oz [489 g]
- Weight

What's in the Box

- Included in Package 1 - Gigabit Ethernet fiber media converter w/ open SFP slot
- 1 - universal power adapter (NA/EU/UK/AU)