

TP-Link VIGI C400HP-4 Turret IP kamera



3MP, 1/2.7" CMOS, Ethernet (100Mb/s), PoE, forgatható, 2304x1296, 30fps, mozgásérzékelő, éjszakai mód, fehér, H.264;H.265, 195g

Cikkszám: VIGI C400HP (4MM)

Ár:

29 310 Ft

Garancia: 2 Év

Security Protocol API Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF

Simultaneous Live View 4 Main Streams & 3 Sub-Streams,
or 3 Main Streams & 5 Sub-Streams

GENERAL

Certification CE, FCC, RCM, BSMI, VCCI, IP67, RoHS

Dimensions(H X W X D)123 × 123 × 83 mm

Materia Plastic

Weight 195 g

Power Requirements 12V DC ± 5%, 5.5mm Coaxial Power Plug
PoE (802.3af/at, class 0)

General Features Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening

CAMERA

Image Sensor 1/2.7" Progressive Scan CMOS

Lens 4 mm / 2.8 mm

Aperture 4 mm: F2.4
2.8 mm: F2.0

Lens Mount M12

Viewing Angle 4 mm, horizontal FOV: 92°, vertical FOV: 48°, diagonal FOV: 114°
2.8 mm, horizontal FOV: 105°, vertical FOV: 56°, diagonal FOV: 125°

Day/Night Mechanism IR Cut Filter

IR Working Distance 30m

Minimum Illumination Color: 0.1 Lux@F2.0; 0 Lux with IR

Pan/Tilt Range Pan: 0° to 360°, Tilt: 0° to 85°, Rotate: 0° to 360°

Digital Noise Reduction3D DNR

WDR DWDR

VIDEO/IMAGE

Video Compression Main stream: H.265/H.264
Sub-Stream: H.265/H.264

Frame Rate & Resolutions Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Resolution: 2304x1296, 2048x1280, 1920x1080, 1280x720, 704x576, 640x480, 352x288, 320x240

Image Enhancement BLC/3D DNR/Prevent Overexposure to Infrared Light

Image Settings Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance
Adjustable by Client Software

Video Bit Rate 64 Kbps to 6 Mbps

SMART FEATURE-SET

Smart Event Area Intrusion Detection, Line-Crossing Detection

Basic Event

Linkage Method

Region of Interest

INTERFACES

Network Interface

Button

Video Output

Motion Detection, Video Tampering Detection, Exception (illegal login)
Trigger Notification: ONVIF, HTTPS
1 Region

1 RJ45 10/100M Self-Adaptive Ethernet Port
-
-

látószög	92°
Gyártó	TP-Link