

TP-Link Archer T2E 200+433Mb/s PCIe x1 Dual-Band Wi-Fi hálózati adapter



IEEE 802.11a/b/g/n/ac (Wi-Fi 5), antennák száma: 1db, antenna: külső
lecsatlakozható, PCI-E x1: 1db

Cikkszám: ARCHER T2E

Ár:

11 860 Ft

Garancia: 3 Év

Interface PCI Express

Dimensions 4.76 × 3.09 × 0.85 in (120.8 × 78.5 × 21.5 mm)

Antenna 1 Detachable External Antenna

WIRELESS FEATURES

Wireless Standards IEEE 802.11b/g/n 2.4 GHz, IEEE 802.11a/n/ac 5 GHz
5 GHz:

11ac: Up to 433 Mbps(dynamic)

11n: Up to 200 Mbps(dynamic)

11a: Up to 54 Mbps(dynamic)

Signal Rate

2.4 GHz:

11n: Up to 200 Mbps(dynamic)

11g: Up to 54 Mbps(dynamic)

11b: Up to 11 Mbps(dynamic)

5GHz:

11ac HT80:-59.0dBm

11n HT40:-68.0dBm

11a 54Mbps:-73.0dBm

Reception Sensitivity

11a 6Mbps:-90.0dBm

2.4GHz:

11n HT40:-70dBm

11g 54Mbps:-75dBm

11b 11Mbps:-87dBm

Transmit Power

5GHz:18dBm(FCC)/23dBm(CE)(EIRP)

2.4GHz:18dBm(FCC)/20dBm(CE)(EIRP)

Wireless Modes

Infrastructure mode

Wireless Security

WEP, WPA/WPA2/WPA3, WPA-PSK/WPA2-PSK/WPA3-SAE

Modulation TechnologyDBPSK, DQPSK, CCK, OFDM, 16-QAM, 64-QAM, 256-QAM

OTHERS

Certification

FCC, CE, RoHS

AC600 Wireless Dual Band PCI Express Adapter

Archer T2E

Package Contents

Low-Profile Bracket

Quick Installation Guide

Resource CD

System RequirementsWindows 10

Operating Temperature: 0?~40? (32? ~104?)

Environment

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing

Dual-Band	Van
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac (Wi-Fi 5)
Wi-Fi titkosítás	WPA2;WPA3;WPA-PSK/WPA2-PSK;WPA3-SAE
Gyártó	TP-Link
antenna	külső lecsatolható
antennák száma	1
átviteli sebesség	600Mb/s
csatlakozás	PCIe x1
PCI-E x1	1 db
WI-FI	Van