Szanex Computer webshop

Szanex Bt.

Cégjegyzék szám: 05-06-005646 Adószám: 21302541-2-05 3700 Kazincbarcika, Dózsa Gy. út 24. szanex@szanex.hu (48) 512-880

StarTech Dual Port PCI-E x1 10/100/1000Mbps hálózati szerver adapter low profile

RJ45: 2db, PCI-E x1: 1db Cikkszám: ST1000SPEXD4

Ár:



70 500 Ft

The ST1000SPEXD4 PCI Express Dual-Port Gigabit Network Card lets you add two gigabit Ethernet ports to a client, server or workstation through a single PCIe slot. Each port provides 10/100/1000 Mbps capable Ethernet and is fully compatible with IEEE 802.3/u/ab standards.

Suitable for any standard PCI Express-enabled system, the 2-port Ethernet card supports full-duplex flow control for maximum data transfer speeds of up to 2000 Mbps - an ideal 2-port NIC for setting up dual-homed, or multi-homed host configurations providing added security to corporate networks.

The dual-port server adapter is compliant with the PCle 2.0 standard and features support for Jumbo Frames and 802.1q VLAN tagging as well as Wake on LAN (WoL). The adapter includes an optional low-profile / half-height bracket that can be used for installation into a standard or small form-factor computer chassis. Backed by a StarTech.com 2-year warranty and free lifetime technical support.

The StarTech.com Advantage

- Protect critical networked systems with a redundant and independent Gigabit port
- Optimize network traffic with support for advanced features such as Jumbo Frames and VLAN tagging
- Maximize the networking efficiency of your virtualized server, with dedicated ports

Bus Type PCI Express

Card Type Standard Profile (LP bracket incl.)

Chipset ID Realtek - RTL8111E

Asmedia - ASM1182E

Industry Standards IEEE 802.3, IEEE 802.3u, IEEE 802.3ab

PCI Express Base Specification 2.0

Interface RJ45 (Gigabit Ethernet)
Port Style Integrated on Card

Ports 2

Performance

Auto MDIX Yes

Compatible Networks 10/100/1000 Mbps

Full Duplex Support Yes Jumbo Frame Support 9K max.

Maximum Data Transfer 2000 Mbps (full-duplex), 1000 Mbps (half-duplex)

Rate

Supported Protocols IEEE 802.1Q VLAN tagging, IEEE 802.1P Layer 2 Priority Encoding and IEEE 802.3x Full

Duplex Flow Control

Connector(s)

Connector Type(s) 1 - PCI Express x1 Male

External Ports 2 - RJ-45 Female

Software

OS Compatibility Windows ® 10 (32/64), 8.1 / 8 (32/64), 7 (32/64), Vista(32/64), XP(32/64), 2000

Windows® Server 2012, 2008 R2, 2003(32/64)

Mac OS 10.4 and up (Tested up to 10.10) Linux 2.4.x and up (Tested up to 3.5)

Special Notes / Requirements

System and Cable

Available PCI Express slot

Requirements

Indicators

LED Indicators

2 - Green - Link/Activity

2 - Yellow - Gigabit Mode

Environmental

Humidity 10~90% RH

Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature 0°C to 100°C (32°F to 212°F)

Physical Characteristics

Product Height 4.7 in [120 mm]
Product Length 3.6 in [92.6 mm]
Product Weight 1.8 oz [51 g]
Product Width 0.7 in [18 mm]

Packaging Information

Shipping (Package) Weight 4.7 oz [133 g]

What's in the Box

Included in Package 1 - PCle Network Card

1 - Low Profile Bracket

1 - Driver CD

1 - Instruction Manual

Gyártó	StarTech
átviteli sebesség	1Gb/s
csatlakozás	PCle x1
low profile	Van
PCI-E x1	1 db
RJ45	2