

TP-Link TL-SG3452 (T2600G-52TS) JetStream switch

LAN (1Gb/s): 48 port, USB2.0, SFP: 4db, menedzselhető,
energiafelhasználás: 32,8W, szürke

Cikkszám: TL-SG3452 (T2600G-52TS)

Ár:

236 450 Ft



Garancia: 5 Év

HARDWARE FEATURES

Interface

- 48× 10/100/1000 Mbps RJ45 Ports
- 4× Gigabit SFP Slots
- 1× RJ45 Console Port
- 1× Micro-USB Console Port

Fan Quantity

Fanless

Power Supply

100-240 V AC~50/60 Hz

Dimensions (W x D x H)

17.3×8.7×1.7 in.
(440×220×44 mm)

Mounting

Rack Mountable

Max Power Consumption

32.8 W

Max Heat Dissipation

111.9 BTU/h

PERFORMANCE

Switching Capacity

104 Gbps

Packet Forwarding Rate

77.4 Mpps

MAC Address Table

16 K

Jumbo Frame

9 KB

SOFTWARE FEATURES

- 8 priority queues
- 802.1p CoS/DSCP priority
- Queue scheduling
 - SP (Strict Priority)
 - WRR (Weighted Round Robin)
 - SP+WRR
- Bandwidth Control
 - Port/Flow based Rating Limiting
- Smoother Performance
- Action for Flows
 - Mirror (to supported interface)
 - Redirect (to supported interface)
 - Rate Limit
 - QoS Remark
- Link Aggregation
 - Static link aggregation
 - 802.3ad LACP
 - Up to 8 aggregation groups and up to 8 ports per group
- Spanning Tree Protocol
 - 802.1d STP
 - 802.1w RSTP

Quality of Service

L2 and L2+ Features

- 802.1s MSTP
- STP Security: TC Protect, BPDU Filter, BPDU Protect, Root Protect, Loop Protect
 - Loopback Detection
- Port-based
- VLAN based
 - Flow Control
- 802.3x Flow Control
- HOL Blocking Prevention
 - Mirroring
- Port Mirroring
- CPU Mirroring
- One-to-One
- Many-to-One
- Tx/Rx/Both
 - Supports 511 (IPv4, IPv6) IGMP groups
 - IGMP Snooping
- IGMP v1/v2/v3 Snooping
- Fast Leave
- IGMP Snooping Querier
- IGMP Authentication
 - IGMP Authentication

L2 Multicast

- MVR
- MLD Snooping
- MLD v1/v2 Snooping
- Fast Leave
- MLD Snooping Querier
- Static Group Config
- Limited IP Multicast
 - Multicast Filtering: 256 profiles and 16 entries per profile

VLAN

- VLAN Group
- Max 4K VLAN Groups
- 802.1q Tagged VLAN
- MAC VLAN: 12 Entries
- Protocol VLAN: Protocol Template 16, Protocol VLAN 16
- GVRP
- VLAN VPN (QinQ)
- Port-Based QinQ
- Selective QinQ
- Voice VLAN
- Time-based ACL
- MAC ACL
- Source MAC
- Destination MAC
- VLAN ID
- User Priority
- Ether Type
- IP ACL
- Source IP
- Destination IP
- Fragment
- IP Protocol

Access Control List

- TCP Flag
- TCP/UDP Port
- DSCP/IP TOS
- User Priority
- Combined ACL
- Packet Content ACL
- IPv6 ACL
- Policy
- Mirroring
- Redirect
- Rate Limit

Security

- QoS Remark
- ACL apply to Port/VLAN
- IP-MAC-Port Binding
- DHCP Snooping
- ARP Inspection
- IPv4 Source Guard
- IPv6-MAC-Port Binding
- DHCPv6 Snooping
- ND Detection
- IPv6 Source Guard
- DoS Defend
- Static/Dynamic Port Security
- Up to 64 MAC addresses per port
- Broadcast/Multicast/Unicast Storm Control
- kbps/ratio/pps control mode
- IP/Port/MAC based access control
- 802.1X
- Port based authentication
- Mac based authentication
- VLAN Assignment
- MAB
- Guest VLAN
- Support Radius authentication and accountability
- AAA (including TACACS+)
- Port Isolation
- Secure web management through HTTPS with SSLv3/TLS 1.2
- Secure Command Line Interface (CLI) management with SSHv1/SSHv2
- IPv6 Dual IPv4/IPv6
- Multicast Listener Discovery (MLD) Snooping
- IPv6 ACL
- IPv6 Interface
- Static IPv6 Routing
- IPv6 neighbor discovery (ND)
- Path maximum transmission unit (MTU) discovery
- Internet Control Message Protocol (ICMP) version 6
- TCPv6/UDPv6

IPv6

- IPv6 applications
- DHCPv6 Client
- Ping6
- Tracert6
- Telnet (v6)
- IPv6 SNMP
- IPv6 SSH
- IPv6 SSL
- Http/Https
- IPv6 TFTP
- 16 IPv4/IPv6 Interfaces
- Static Routing
- 48 static routes
- Static ARP
- 316 ARP Entries
- Proxy ARP
- Gratuitous ARP
- DHCP Server
- DHCP Relay
- DHCP L2 Relay
- Web-based GUI
- Command Line Interface (CLI) through console port, telnet
- SNMPv1/v2c/v3
- Trap/Inform

L3 Features

Management	- RMON (1, 2, 3, 9 groups) • SDM Template • DHCP/BOOTP Client • 802.1ab LLDP/LLDP-MED • DHCP AutoInstall • Dual Image, Dual Configuration • CPU Monitoring • Cable Diagnostics • EEE • Password Recovery • SNTP • System Log • Support Omada Hardware Controller (OC200/OC300), Software Controller, Cloud-Based Controller
	• Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule • ZTP (Zero-Touch Provisioning)*
OTHERS	
Certification	CE, FCC, RoHS • TL-SG3452 Switch • Power Cord
Package Contents	• Quick Installation Guide • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0–40 ° (32–104 °); • Storage Temperature: -40–70 ° (-40–158 °) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

energiafelhasználás	32.8
SFP	4
Gyártó	TP-Link