

TP-Link EAP650 AX3000 Dual-Band Wi-Fi PoE access point (ceiling mount)



2976Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 1 port, 5dBi, Mesh Wi-Fi, energiafelhasználás: 13,5W, fehér

Cikkszám: EAP650

Ár:

70 660 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	1× Gigabit Ethernet (RJ-45) Port (supports IEEE802.3at PoE)
Button	Reset
Power Supply	• 802.3at PoE • 12 V / 1.0 A DC (EU), 12 V / 1.5 A DC (US)
Power Consumption	• EU: 13.5 W • US: 14.7 W
Dimensions (W x D x H)	6.3 × 6.3 × 1.3 in (160 × 160 × 33.6 mm)
Antenna Type	Internal Omni • 2.4 GHz: 2× 4 dBi • 5 GHz: 2× 5 dBi
Mounting	• Ceiling /Wall Mounting (Kits included) • Junction Box Mounting

WIRELESS FEATURES

Wireless Standards	IEEE 802.11ax/ac/n/g/b/a
Frequency	2.4 GHz and 5 GHz
Signal Rate	• 5 GHz: Up to 2402 Mbps • 2.4 GHz: Up to 574 Mbps • 1024-QAM • 4× Longer OFDM Symbol • OFDMA • Multiple SSIDs (Up to 16 SSIDs, 8 for each band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • MU-MIMO
Wireless Functions	• HE160 (160 MHz Bandwidth)[‡] • Seamless Roaming[§] • Omada Mesh[§] • Band Steering • Load Balance • Airtime Fairness • Beamforming • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client

Wireless Security	• Captive Portal Authentication [§]
	• Access Control
	• Wireless Mac Address Filtering
	• Wireless Isolation Between Clients
	• SSID to VLAN Mapping
Transmission Power	• Rogue AP Detection
	• 802.1X Support
	• WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise
	• CE:
	<20 dBm(2.4 GHz, EIRP)
	<23 dBm(5 GHz, Band1 & Band2, EIRP)
	<30 dBm(5 GHz, Band3, EIRP)
	• FCC:
	<25 dBm (2.4 GHz)
	<25 dBm (5 GHz)
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller (OC300)
	• Omada Hardware Controller (OC200)
	• Omada Software Controller
	• Omada Cloud-Based Controller
Cloud Access	Yes (Through OC300, OC200, Omada Software Controller, or Omada Cloud-Based Controller)
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c, v3
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• EAP650
	• Power Adapter
	• Ceiling/Wall Mounting Kits
	• Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Linux
Environment	• Operating Temperature: 0-40 ° (32-104 °)
	• Storage Temperature: -40-70 ° (-40-158 °)
	• Operating Humidity: 10-90% RH non-condensing
	• Storage Humidity: 5-90% RH non-condensing

Dual-Band	Van
energiafelhasználás	13.5
LAN (1Gb/s)	1
Mesh Wi-Fi	Van
PoE port	1
Wi-Fi átviteli sebesség	2976
Wi-Fi jel típus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)

Wi-Fi titkosítás	WPA3;WPA3-Enterprise
Gyártó	TP-Link
antenna nyeresége	5
antenna típusa	belső
cikknév kiegészítés	(ceiling + wall mount)
PoE	Van
WI-FI	Van
szín	fehér