

TP-Link TL-SG1210P PoE switch

LAN (1Gb/s): 9 port, SFP: 1db, energiafelhasználás: 78,13W, szürke
Cikkszám: TL-SG1210P

Ár:
44 280 Ft



Garancia: 5 Év

HARDWARE FEATURES

Interface	8 PoE+ 10/100/1000Mbps RJ45 Ports 1 10/100/1000Mbps RJ45 Port 1 Gigabit SFP Slot 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-X MMF, SMF
Network Media	
Fan Quantity	Fanless
Physical Security Lock	Yes
Power Supply	External Power Adapter(Output: 53.5VDC / 1.31A)
Backup Bandwidth	20 Gbps
PoE+ Ports(RJ45)	Standard: 802.3at/802.3af compliant PoE Ports: Port1- Port 8 PoE Power Budget: 63W
Mac Address Table	4K
Dimensions (W x D x H)	209 × 126 × 26 mm
Max Power Consumption	7.11 W (220/50Hz. no PD connected) 78.13 W (220/50Hz. with 63W PD connected)
Max Heat Dissipation	24.25 BTU/h (no PD connected) 266.42 BTU/h (with 63W PD connected)

SOFTWARE FEATURES

Advanced Features	Compatible With IEEE 802.3af/at Compliant PDs EEE802.3x Flow Control 802.1p/DSCP QoS IGMP Snooping
-------------------	---

Transmission MethodStore-And-Forward

OTHERS

Certification	CE, FCC, RoHS
Package Contents	TL-SG1210P, Power Adapter, Installation Guide
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~70°C (-40°F~158°F) Operating Humidity: 10% ~ 90% non-condensing Storage Humidity: 5%~90% non-condensing

