

TP-Link TL-SG105PE switch

LAN (1Gb/s): 5 port, energiafelhasználás: 2,3W, szürke

Cikkszám: TL-SG105PE

Ár:

25 160 Ft



Garancia: 5 Év

Standards and Protocols	IEEE 802.3i, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.1q, IEEE 802.1p, IEEE 802.3at
Interface	Five 10/100/1000Mbps RJ45 Ports AUTO Negotiation/AUTO MDI/MDIX 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Network Media	100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
Fan Quantity	Fanless
Power Supply	External Power Adapter (Output: 53.5 VDC/1.31 A) Standard: 802.3 af/at compliant
PoE Ports (RJ45)	PoE Ports: Port 1- Port 4 PoE Power Budget: 65 W
Max Power Consumption	4.52 W (220V/50Hz with no PD connected) 75.16 W (220V/50Hz with 65 W PD connected)
Max Heat Dissipation	15.41 BTU/h (with no PD connected) 256.30 BTU/h (with 65 W PD connected)
PERFORMANCE	
Switching Capacity	10 Gbps
Packet Forwarding Rate	7.44 Mpps
MAC Address Table	2 K
Packet Buffer Memory	1.5 Mb
Jumbo Frame	16 KB
SOFTWARE FEATURES	
Quality of Service	Support Port-Based/802.1p/DSCP priority Support 4 priority queues Rate Limit Storm Control IGMP Snooping V1/V2/V3 Static Link Aggregation Port Mirroring
L2 Features	Cable Diagnostics Loop Prevention PoE Auto Recovery Extend Mode
VLAN	Supports up to 32 VLANs simultaneously (out of 4K VLAN IDs) MTU/Port/Tag VLAN

Management	Web-based GUI Easy Smart Configuration Utility
Transmission Method	Store-And-Forward
OTHERS	
Certification	FCC, CE, RoHS TL-SG105PE
Package Contents	Power Adapter Installation Guide Rubber Feet
System Requirements	Microsoft® Windows® for running Utility Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?)
Environment	Operating Humidity: 10%~90%RH non-condensing Storage Humidity: 5%~95%RH non-condensing