

Ubiquiti UniFi 6 Pro AX5400 Dual-Band Wi-Fi PoE access point (wall mount)



5373Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 1 port, Bluetooth, 6dBi, energiafelhasználás: 13W, fehér, IP54

Cikkszám: U6-PRO

Ár:

83 340 Ft

Garancia: 2 Év

- **POE TÁPEGYSÉG NÉLKÜL!**
- Dual-band WiFi 6 (802.11ax)
- 5 GHz (4x4 MU-MIMO) band with a 4.8 Gbps throughput rate
- 2.4 GHz (2x2 MIMO) band with a 573.5 Mbps throughput rate
- Operates at full 4x4 MIMO with 160 MHz bandwidth
- 300+ concurrent client capacity
- Guest Traffic Isolation, which enhances wireless network security and lowers traffic congestion
- Included universal mounting plate, backing plate, and screw kit

Mechanical

Dimensions	O197 x 35 mm (O7.76 x 1.38")
Weight	Without mount: 460 g (1.01 lb) With mount: 600 g (1.32 lb)
Enclosure material	Plastic
Mounting material	SGCC steel
Weatherproofing	IP54

Hardware

Management interfaces	Ethernet Bluetooth
Networking interface	(1) GbE RJ45 port
Button	Factory reset
LEDs	White/Blue
Power method	802.3at PoE+
Power supply	UniFi PoE switch 48V, 0.5A PoE adapter (not included)

Supported voltage range	44 to 57VDC
Max. power consumption	13W
Max. TX power	
2.4 GHz	22 dBm
5 GHz	26 dBm
MIMO	
2.4 GHz	2 x 2 (UL MU-MIMO)
5 GHz	4 x 4 (DL/UL MU-MIMO)
Throughput rate	
2.4 GHz	573.5 Mbps
5 GHz	4.8 Gbps
Antenna gain	
2.4 GHz	4 dBi
5 GHz	6 dBi
Mounting	Wall/ceiling (included)
Operating temperature	-30 to 60° C (-22 to 140° F)
Operating humidity	5 - 95% noncondensing
Certifications	CE, FCC, IC

Software

WiFi standards	802.11a/b/g WiFi 4/WiFi 5/WiFi 6
Wireless security	WPA-PSK, WPA-Enterprise (WPA/WPA2/WPA3)
BSSID	8 per radio
VLAN	802.1Q
Advanced QoS	Per-user rate limiting
Guest traffic isolation	Supported
Concurrent clients	300+
Zero wait DFS	Yes*
	*Supported with upcoming firmware versions

Supported Data Rates

802.11a	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11b	1, 2, 5.5, 11 Mbps
802.11g	6, 9, 12, 18, 24, 36, 48, 54 Mbps
802.11n (WiFi 4)	6.5 Mbps to 600 Mbps (MCS0 - MCS31, HT 20/40)
802.11ac (WiFi 5)	6.5 Mbps to 3.4 Gbps (MCS0 - MCS9 NSS1/2/3/4, VHT 20/40/80/160)
802.11ax (WiFi 6)	7.3 Mbps to 4.8 Gbps (MCS0 - MCS11 NSS1/2/3/4, HE 20/40/80/160)

cikknév kiegészítés 2	IP54
Dual-Band	Van
energiafelhasználás	13
LAN (1Gb/s)	1
PoE port	1
tömeg	600
Wi-Fi átviteli sebesség	5373
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)

Wi-Fi titkosítás	WPA3;WPA3-Enterprise;WPA2-PSK;WPA2-Enterprise
Gyártó	Ubiquiti
antenna nyeresége	6
antenna típusa	belső
Bluetooth	Van
cikknév kiegészítés	(wall mount)
PoE	Van
WI-FI	Van
szín	fehér