

TP-Link TL-SG1218MP PoE rack switch

LAN (1Gb/s): 18 port, SFP: 2db, energiafelhasználás: 286,64W, fekete
Cikkszám: TL-SG1218MP

Ár:
115 090 Ft



Garancia: 5 Év	
Standards and Protocols	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3x, IEEE 802.3af, IEEE 802.3at, IEEE 802.1q, IEEE 802.1p
Interface	• 16× PoE+ gigabit RJ45 ports • 2× gigabit non-PoE RJ45 ports • 2× combo gigabit SFP slots
Network Media	• 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 100BASE-TX: UTP category 5, 5e cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m) • EIA/TIA-568 100Ω STP (maximum 100m) • 1000BASE-X MMF, SMF
Fan Quantity	2
Physical Security Lock	Yes
Power Supply	100-240 VAC, 50/60 Hz • Standard: 802.3at/802.3af compliant
PoE+ Ports(RJ45)	• PoE Ports: Ports 1-16 • PoE Power Budget: 250 W
Dimensions (W x D x H)	17.3 × 7.1 × 1.73 in (440 × 180 × 44 mm)
Mounting	Rack Mountable
Max Power Consumption	• 21.4 W (220/50 Hz. no PD connected) • 286.64 W (220/50 Hz. with 250 W PD connected) • 72.97 BTU/h (no PD connected) • 977.44 BTU/h (with 250 W PD connected)
Max Heat Dissipation	
PERFORMANCE	
Switching Capacity	36 Gbps
Packet Forwarding Rate	26.78 Mbps
MAC Address Table	8K
Packet Buffer Memory	4.1 Mbit • Compatible With IEEE 802.3af/at Compliant PDs • 802.1p/DHCP QoS
Advanced Functions	• Mac Address Auto-Learning And Auto-Aging • IEEE802.3x Flow Control For Full-Duplex Mode And Backpressure For Half-Duplex Mode
Jumbo Frame	10 KB
OTHERS	

Certification	CE, FCC, RoHS • TL-SG1218MP • Installation Guide
Package Contents	• Power Cord • Rackmount Kit • Rubber Feet
Environment	• Operating Temperature: 0-50 °C (32-122 °F) • Storage Temperature: -40-70 °C (-40-158 °F) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing