

TP-Link EAP650-Wall AX3000 Dual-Band Wi-Fi PoE access
point (wall-plate mount)



2976Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 2 port, 5dBi,
Mesh Wi-Fi, energiafelhasználás: 11,5W, fehér

Cikkszám: EAP650-WALL

Ár:

56 680 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface

- Uplink: 1× 10/100/1000 Mbps Ethernet Port
- Downlink: 1× 10/100/1000 Mbps Ethernet Port

Physical Security LockNo

Button

Reset, LED

Power Supply

802.3af/at PoE

Power Consumption

EU: 11.5 W

Dimensions

86 × 86 × 42.6 mm (3.4 × 3.4 × 1.7 in)

Antenna

2 Dual-Band Antennas

- 2.4 GHz: 2× 3 dBi
- 5 GHz: 2× 5 dBi

Mounting

Wall Plate Mounting (Kits included)

WIRELESS FEATURES

Concurrent Clients 100+

Wireless Standards IEEE 802.11ax/ac/n/g/b/a

Frequency 2.4 GHz and 5 GHz

Signal Rate

- 5 GHz: Up to 2402 Mbps
- 2.4 GHz: Up to 574 Mbps
- 16 SSIDs (Up to 8 SSIDs on each band)
- Enable/Disable Wireless Radio
- Automatic Channel Assignment
- Transmit Power Control (Adjust Transmit Power on dBm)
- QoS(WMM)
- Seamless Roaming[§]
- Beamforming
- Rate Limit

Wireless Functions

- Load Balance
- Airtime Fairness
- Band Steering
- Reboot Schedule
- Wireless Schedule
- RADIUS Accounting
- MAC Authentication
- Wireless Statistics
- Static IP/Dynamic IP
- Captive Portal Authentication[§]
- Access Control
- Wireless Mac Address Filtering

Wireless Security	• Wireless Isolation Between Clients • VLAN • Rogue AP Detection • 802.1X Support • WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise • CE:
Transmission Power	<20 dBm (2.4GHz, EIRP) <22 dBm (5GHz band1 & 2, EIRP) <22 dBm (5GHz band3, EIRP)
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller • Omada Cloud-Based Controller
Cloud Access	Yes. Requiring the use of OC300, OC200, Omada Cloud-Based Controller, or Omada Software Controller.
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c, v3
System Logging	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller.
OTHERS	
Certification	CE, RoHS
Package Contents	• AX3000 Wall Plate WiFi 6 Access Point EAP650-Wall • Installation Guide • Mounting Kits
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows 11, Linux
Environment	• Operating Temperature: 0-40 ° (32-104 °) • Storage Temperature: -40-70 ° (-40-158 °) • Operating Humidity: 10-90% RH non-condensing • Storage Humidity: 5-90% RH non-condensing