

## Asus ProArt PA248QV 24.1" IPS LED monitor (100% sRGB, DeltaE<2) fekete



24,1", 1920x1200, 16:10, 300cd/m2, 1000:1, 5ms, USB3.0, D-Sub, HDMI, DisplayPort, hangszóró, falra szerelhető (VESA), portré mód (pivot), forgatható (swivel), dönthető (tilt), 15W

Cikkszám: 90LM05K1-B01370

Ár:

132 240 Ft

Garancia: 3 Év

- Display

**Panel Size:** Wide Screen 24.1"(61.13cm) 16:10

**Color Saturation :** 100% sRGB / 100% Rec. 709

**Panel Type :** IPS

**True Resolution :** 1920x1200

**Display Viewing Area(HxV) :** 518.4 x 324.0 mm

**Display Surface :** Non-glare

**Pixel Pitch :** 0.270mm

**Brightness(Max) :** 300 cd/?

**Contrast Ratio (Max) :** 1000:1

**ASUS Smart Contrast Ratio (ASCR) :** 100000000:1

**Viewing Angle (CR?10) :** 178°(H)/178°(V)

**Response Time :** 5ms (Gray to Gray)

**Display Colors :** 16.7M

**Flicker free :** Yes

- Video Feature

**Trace Free Technology :** Yes

**ProArt Preset :** 9 Modes(sRGB Mode/Rec. 709 Mode/Scenery Mode/Standard Mode/Rapid Rendering/User Mode 1/User Mode 2/Reading Mode/Darkroom Mode)

**ProArt Palette :** Yes

**Skin-Tone Selection :** 3 Modes

**Color Temperature Selection :** 4 Modes

**Color Accuracy :** ?E< 2

**Gamma adjustment :** Yes (Support Gamma 1.8/2.0/2.2/2.4/2.6 )

**Color Adjustment :** 6-axis adjustment(R,G,B,C,M,Y)

**QuickFit (modes) :** Yes (Alignment Grid/Paper/Ruler Modes)

**Low Blue Light :** Yes

**HDCP support :** Yes, 1.4

**Adaptive-Sync supported :** Yes

**Motion Sync:** Yes

- Audio Features

**Stereo Speakers :** 2W x 2 Stereo RMS

- I/O Ports

**Signal Input :** HDMI, D-Sub, DisplayPort

**PC Audio Input :** 3.5mm Mini-Jack

**Earphone jack :** 3.5mm Mini-Jack

**USB Port(s) :** 3.0x4

- Signal Frequency

**Analog Signal Frequency** : 30 ~105 KHz (H) /49 ~75 Hz(V)

**Digital Signal Frequency** : 30 ~105 KHz (H) /49 ~75 Hz(V)

- Power Consumption  
Power Consumption:<15W\*  
Power Saving Mode:<0.5W  
Power Off Mode:0W(hard switch)  
Voltage: 100–240V, 50 / 60 Hz
- Mechanical Design  
**Chassis Colors** : Black  
**Tilt** : -5°~+35°  
**Swivel** : +90°~-90°  
**Pivot** : +90°~-90°  
**Height Adjustment** : 0~130 mm  
**VESA Wall Mounting** : 100x100mm  
**Quick Release Stand Design** : Yes
- Security  
Kensington lock
- Dimensions  
Phys. Dimension with Stand (WxHxD) : 533 x (375 - 505) x 211 mm  
Phys. Dimension without Stand (WxHxD) : 533 x 360 x 47 mm  
Box Dimension (WxHxD) : 649 x 474 x 192 mm
- Weight  
Net Weight (Esti.) : 6.1 kg, Without Stand (Esti.) : 3.9 Kg,  
Gross Weight (Esti.) : 8.3 kg
- Accessories  
VGA cable(Optional)  
Audio cable(Optional)  
Power cord  
DisplayPort cable (Optional)  
USB cable(Optional)  
Quick start guide  
HDMI cable (Optional)  
Warranty Card  
Color pre-calibration report  
Welcome Card
- Compliance and Standards  
Energy Star®, BSMI, CB, CCC, CE, CU, ErP, FCC, ISO-9241-307, J-MOSS, KCC, PSB, PSE, RoHS, TCO8.0, TUV-Ergo, TUV-GS, UL/cUL, VCCI, WEEE, WHQL (Windows 10, Windows 7), MEPS, RCM, TUV Flicker-free , KC , eStandby, TUV Low Blue Light, ICES-3, PC recycle, CEC
- Note  
\* Adaptive-Sync only can be activated within “48Hz ~ 75Hz” via HDMI and DisplayPort ports  
\*To activate Rapid Rendering needs turn off Adaptive-Sync and only be activated at 75Hz. Brightness, Blue Light Filter, ASCR, Trace Free cannot be adjusted when using this function.  
\*measuring a screen brightness of 200 nits without audio/ USB/ Card reader connection

|                         |      |
|-------------------------|------|
| falra szerelhető (VESA) | Van  |
| Gyártó                  | Asus |