

TP-Link TL-SG1005LP PoE switch

LAN (1Gb/s): 5 port, energiafelhasználás: 47,5W, szürke

Cikkszám: TL-SG1005LP

Ár:

15 640 Ft



Garancia: 5 Év

Interface

- 5× 10/100/1000Mbps RJ45 Ports

- AUTO Negotiation

- AUTO MDI/MDIX

- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)

- EIA/TIA-568 100Ω STP (maximum 100m)

- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)

- EIA/TIA-568 100Ω STP (maximum 100m)

- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)

- EIA/TIA-568 100Ω STP (maximum 100m)

Network Media

Fan Quantity

Fanless

External Power Supply

External Power Adapter (Output: 53.5 VDC / 0.81 A)

Packet Forwarding Rate

7.44 Mpps

- Standard: 802.3 af/at compliant

PoE Ports (RJ45)

- PoE Ports: Ports 1-4

- Power Supply: 40 W

Mac Address Table

2K

Jumbo Frame

16 KB

Switching Capacity

10 Gbps

Dimensions (W x D x H)

3.9×3.9×1.0 in (99.8×98×25 mm)

Max Power Consumption

- 4.12 W (220/50 Hz. no PD connected)

- 47.5 W (220/50 Hz. with 40 W PD connected)

Max Heat Dissipation

- 14.05 BTU/h (no PD connected)

- 161.98 BTU/h (with 40 W PD connected)

SOFTWARE FEATURES

- Compatible With IEEE 802.3af/at Compliant PDs

- Mac Address Auto-Learning And Auto-Aging

Advanced Features

- IEEE 802.3x Flow Control

- 802.1p/DSCP QoS

- IGMP Snooping

Transfer Method

Store-And-Forward

OTHERS

Certification

FCC, CE, RoHS

- TL-SG1005LP

Package Contents

- Power Adapter

- Installation Guide

- Operating Temperature: 0-40 ° (32-104 °);

- Storage Temperature: -40-70 ° (-40-158 °)

Environment

- Operating Humidity: 10-90% RH non-condensing
- Storage Humidity: 5-90% RH non-condensing

