

TP-Link EAP223 AC1350 Dual-Band Wi-Fi PoE access point (ceiling/wall mount)



1317Mb/s, IEEE 802.11a/b/g/n/ac (Wi-Fi 5), LAN (1Gb/s): 1 port, antennák száma: 3db, 5dBi, Mesh Wi-Fi, energiafelhasználás: 9,7W, fehér

Cikkszám: EAP223

Ár:

44 960 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	Gigabit Ethernet (RJ-45) Port×1 (Support IEEE802.3af/at PoE and Passive PoE)
Physical Security Lock Button	Yes Reset
Power Supply	• 802.3af/at PoE • 48V Passive PoE (+4,5pins; -7,8pins. PoE Adapter IS NOT Included)
Power Consumption	EU: 9.7W US: 12.1W
Dimensions (W x D x H)	8.1 × 7.1 × 1.5 in (205.5 × 181.5 × 37.1 mm) 3 Internal Omni
Antenna Type	• 2.4 GHz: 4 dBi • 5 GHz: 5 dBi
Mounting	Ceiling /Wall Mounting (Kits included)

WIRELESS FEATURES

Wireless Standards	IEEE 802.11ac/n/g/b/a
Frequency	2.4 GHz and 5 GHz
Signal Rate	• 5 GHz:Up to 867 Mbps • 2.4 GHz:Up to 450 Mbps • Multiple SSIDs (Up to 15 SSIDs, 8 for 2.4GHz band, 7 for 5GHz band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Seamless Roaming* • Omada Mesh*
Wireless Functions	• Band Steering • Load Balance • MU-MIMO • Airtime Fairness • Beamforming • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client • Captive Portal Authentication* • Access Control
Wireless Security	• Wireless Mac Address Filtering • Wireless Isolation Between Clients

	• SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • CE:
Transmission Power	≤20 dBm(2.4 GHz, EIRP)
	≤23 dBm(5 GHz, EIRP)
	• FCC:
	≤24 dBm(2.4 GHz)
	≤22 dBm(5 GHz)
MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller OC300 • Omada Hardware Controller OC200 • Omada Software Controller • Omada Cloud-Based Controller
	Yes, through
	• OC300 • OC200
Cloud Access	• Omada Software Controller • Omada Cloud-Based Controller
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1,v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point EAP223
	• Mounting Kits
	• Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Environment	• Operating Temperature: 0–40 ° (32–104 °)
	• Storage Temperature: -40–70 ° (-40–158 °)
	• Operating Humidity: 10–90% RH non-condensing
	• Storage Humidity: 5–90% RH non-condensing

Dual-Band	Van
energiafelhasználás	9.7
LAN (1Gb/s)	1
Mesh Wi-Fi	Van
PoE port	1
Wi-Fi átviteli sebesség	1317
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac (Wi-Fi 5)
Gyártó	TP-Link
antenna nyeresége	5
antenna típusa	belső

antennák száma	3
cikknév kiegészítés	(ceiling/wall mount)
PoE	Van
WI-FI	Van
szín	fehér