

Delock mini PCI-E x1 2+1 portos soros port párhuzamos port multi IO vezérlő

illesztés: Mini PCIe x1, soros port: 2db, párhuzamos port: 1db

Cikkszám: 95246

Ár:

41 010 Ft



This MiniPCIe adapter by Delock expands your system by two additional serial and one parallel port, which you can lead out through the slot bracket. You can connect different serial and parallel devices like printer, scanner, modem etc. to this adapter.

Specification

- Connector:
on the module:
 - 2 x 10 pin pin header male (serial)
 - 1 x 18 pin pin header male (parallel)on the slot bracket (standard) 2 x:
 - 2 x serial RS-232 DB9 male with screw nuts
 - 1 x parallel male with screw nutsor on the slot bracket (low profile) 3 x:
 - 1 x serial RS-232 DB9 male with screw nuts
 - 1 x parallel male with screw nuts
- Chipset: Systembase SB16C1053
- Form factor: MiniPCIe full size
- Interface: PCI Express revision 2.0
- Data transfer rate up to 921.6 Kb/s
- Compatible with 16C550 UART
- Cable length: ca. 30 cm (incl. connector)

System requirements

- Windows Vista/Vista-64/7/7-64/8/8-64/8.1/8.1-64, Linux Kernel 2.6
- Mainboard with a free MiniPCIe slot with a PCIe interface

Package content

- MiniPCIe module
- 2 x serial connection cable (pin header > DB9)
- 1 x parallel connection cable (pin header > DB25)
- Power cable
- 2 x standard slot bracket
- 3 x low profile slot bracket
- Driver CD
- User manual

Package

- Box

