

TP-Link VIGI C340 Bullet smart home kültéri IP kamera (IP66)



4MP, 2,8mm F1.6 1/3" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 2560x1440, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+, 195g

Cikkszám: VIGI C340 (2.8MM)

Ár:

31 100 Ft

HÁLÓZAT

Biztonság	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
Szabvány	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
API	ONVIF
Simultaneous Live View	3 Main Streams & 3 Sub-Streams

ÁLTALÁNOS

	VIGI Network Camera
Csomagolás tartalma	Quick Start Guide Waterproof Cable Attachments Mounting Accessories (Screws, Drywall Anchors, Hex Key)

Operating Temperature	-30-60 °C
Certifications	CE, RCM, BSMI, VCCI, RoHS, NTRA, KC
Méret (Ma x Sz x Mé)	78 x 70 x 174 mm
Material	Plastic
Tömeg	195g
General Features	Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening
Power Supply	12V DC $\pm$ 5%, 5.5mm Coaxial Power Plug PoE (802.3af/at, class 0)
Power Consumption	12V DC: Max 7.5W PoE: Class 0

KAMERA

Képzékelő	1/3" Progressive Scan CMOS
Optika	Fixed focal lens (2.8 mm / 4 mm / 6 mm) 2.8 mm: F1.6 4 mm: F1.6 6 mm: F1.6
Aperture	
Lens Mount	M12
Látószög	(2.8mm) Horizontal FOV: 102°, Vertical FOV: 55°, Diagonal FOV: 122° (4mm) Horizontal FOV: 79°, Vertical FOV: 43°, Diagonal FOV: 93° (6mm) Horizontal FOV: 50°, vertical FOV: 27°, Diagonal FOV: 59°
Day/Night Mechanism	IR Cut Filter
IR Working Distance	30m
Illumination Distance	30 m
Min. szükséges megvilágítás	0 lux with IR/white Light

Weatherproof Rating	IP66
Digital Noise Reduction	3D DNR
WDR	DWDR

VIDEÓ/KÉP

Main stream: H 265+/H 265/H 264+/H 264

Videó tömörítés	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264 Main Stream Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080
Kép frissítés (frame) és felbontás	Sub-Stream Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480, 352x288, 320x240
Videótovábbítás	Main Stream Sub-Stream
Képbeállítás	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software
Image Enhancement	BLC/3D DNR/Prevent Overexposure to Infrared Light
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps Sub-Stream: 64 Kbps to 512 Kbps
SMART FEATURE-SET	
Smart Event	Area Intrusion Detection, Line-Crossing Detection, Human Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (illegal login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region
FIZIKAI KEZELŐFELÜLET	
Hálózati csatlakozás	1 RJ45 10/100M Self-Adaptive Ethernet Port
Audio Input	Built-in Microphone
Audio Output	Built-in Speaker
Gomb	Reset Button
Slot	Micro SD card

Gyártó	TP-Link
döntési szög	90
forgatási szög	90
forgatható	Van