

TP-Link VIGI C540-W Bullet Wi-Fi smart home kültéri IP
kamera IP66



4MP, 4mm F1.6 1/3" CMOS, Ethernet (100Mb/s), Wi-Fi, PoE, beépített mikrofon, beépített hangszóró, forgatható, 2560x1440, 30fps, mozgásérzékelő, éjszakai mód, microSD, fehér-fekete, H.265+;H.264+, 195g

Cikkszám: VIGI C540-W (4MM)

Ár:

56 860 Ft

Garancia: 3 Év

NETWORK

Security
Protocol

Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
11 Mbps (802.11b)

Wireless Rate

54 Mbps (802.11g)
150 Mbps (802.11n)

Frequency

2.4 GHz

Wireless Security

WPA/WPA2-PSK

API

ONVIF

Simultaneous Live View

3 Main Streams & 3 Sub-Streams

GENERAL

VIGI Network Camera

Quick Start Guide

Package Contents

Waterproof Cable Attachments

Power Adapter

Mounting Accessories (Screws, Drywall Anchors, Hex Key)

Operating Temperature

-30~60 °C

Certifications

CE, RCM, BSMI, VCCI, RoHS, NCC, JRF, KC

Dimensions(H X W X D)

120 × 172 × 198 mm

Material

Plastic

General Features

Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening

Power Requirements

12V DC ± 5%, 5.5mm Coaxial Power Plug

CAMERA

Image Sensor

1/3" Progressive Scan CMOS

Lens

Fixed focal lens (4 mm)

Aperture

4 mm: F1.6

Lens Mount

M12

Viewing Angle

(4mm) Horizontal FOV: 79°Vertical FOV: 43°Diagonal FOV: 93°

Digital Zoom

Yes

Day/Night Mechanism

IR Cut Filter

IR Working Distance

30m

Illumination Distance

30 m

Minimum Illumination

0 lux with IR/white Light

Pan/Tilt Range

Pan: 0° to 350°, Tilt: 0° to 120°

Weatherproof Rating

IP66

Digital Noise Reduction

3D DNR

WDR

DWDR

VIDEO/IMAGE

Video Compression	Main stream: H.265+/H.265/H.264+/H.264
	Sub-Stream: H.265/H.264
	Main Stream
	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Frame Rate & Resolutions	Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080
	Sub-Stream
	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
	Resolution: 640x480, 352x288, 320x240
Video Streaming	Main Stream
	Sub-Stream
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance
	Adjustable by Client Software
Image Enhancement	BLC/3D DNR/Prevent Overexposure to Infrared Light
Video Bit Rate	Main Stream: 256 Kbps to 4 Mbps
	Sub-Stream: 64 Kbps to 512 Kbps
SMART FEATURE-SET	
Smart Event	Area Intrusion Detection, Line-Crossing Detection, Human Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (illegal login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Audio Input	Built-in Microphone
Audio Output	Built-in Speaker
Button	Reset Button
Slot	Micro SD card

beépített hangszóró	mono
érzékelő felbontása	4MP
látószög	93°
smart home	Van
tömeg	195
videó felbontása	2560x1440
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP66
csatlakozó	Ethernet (100Mb/s)
döntési szög	120
éjszakai mód	Van
érzékelő típusa	4mm F1.6 1/3" CMOS
forgatási szög	350
forgatható	Van
kamera rögzítés típusa	falra és mennyezetre rögzíthető
memóriakártya foglalat	microSD

mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	30
WI-FI	Van
szín	fehér-fekete