

Delock USB-A 2.0 -> Serial-TTL nyitott vezeték Male adatkábel 1.8m fekete 5V

Cikkszám: 83116

Ár:

10 890 Ft



Description

This USB 2.0 Serial-TTL converter by Delock is due to its wide temperature range most suitable for industrial applications. It supports virtual COM ports and enables optional a direct access to the interface. The converter is multifunctional compatible to the standard systems Windows, Linux and MAC. It is suitable for Embedded systems, control systems, Field Programmable Gate Array, MCUs, dongles etc.

Specification

- Connector: USB 2.0 male > Serial-TTL 6 open wires
- Chipset: FTDI 232RL
- Cable gauge: AWG 24
- Temperature range: -20°C to +80°C
- No-load current: 70 uA
- Converter: 5 V / 15 mA (VCC, GND)
- Compatible to UHCI / OHCI / EHCI controller
- TTL 5 V (data) / 4 mA or HighLevel 12 mA
- Features: RemoteWakeup, EEPROM
- Data rate 300 baud - 3 Megabaud
- Databit: 7 or 8
- Stopbits: 1 or 2
- Parity: none, space character, straight, unequal, mark
- Flow control: software XON/XOFF or hardware RTS/CTS
- FIFO: 128 Byte - RX
256 Byte - TX
- Cable length: ca. 1.80 m

System requirements

- Windows CE 4.2, 5.0, 6.0/Windows Mobile 2003/XP/XP-64/Vista/Vista-64/7/7-64, Mac OS 10.5, 10.6, Linux ex Kernel 2.6
- PC or notebook with a free USB port

Package content

- Converter USB 2.0 > Serial-TTL
- Driver CD
- User manual

Package

- Retail Box

Gyártó	Delock
bemeneti csatlakozó	USB-A 2.0
cikknév kiegészítés	5V
csatlakozó típus	Male
hossz	1.8 m
irány	->
kimeneti csatlakozó	Serial-TTL nyitott vezeték
szín	fekete