

# StarTech USB A VGA M/F adapter KVM Console to Laptop Crash Cart Adapter with File Transfer & Video Capture

Cikkszám: NOTECONS02

Ár:

284 210 Ft



The NOTECONS02 Portable USB Crash Cart Adapter lets you turn your laptop into a portable console for rack servers, PCs, ATMs, kiosks and more, now with local file transfer and video capture built into the software. Simply connect the crash cart adapter to your laptop using the included USB cable, then connect the integrated USB and VGA cables to your server for instant, BIOS-level control.



### Connect Quickly

Get connected in seconds. The crash cart adapter offers integrated VGA and USB cables for the server-side connections and includes the USB cable to connect to your laptop.

Troubleshoot your devices faster with a flexible software interface that lets you transfer files from your laptop to the server, capture videos for records or instructional purposes, take screenshots and scale the display window to full screen mode or smaller, with no scroll bars - ever.

### Connect Universally

With no server-side software installation required, the USB crash cart adapter can connect to any PC or device that has a VGA and USB port, to provide BIOS-level control.

Powered from the server-side USB connection, the laptop crash cart adapter doesn't require an AC outlet and saves your laptop / netbook battery power.

### Connect Portably

With portability for the mobile administrator or repair technician in mind, this pocket-sized adapter features a rugged design that easily fits inside your laptop bag and requires no additional accessories to connect.

Eliminating the need to lug around a large, awkward traditional crash cart to troubleshoot and service your systems, this portable crash cart lets you connect to a headless device with only a laptop.

Backed by a StarTech.com 2-year warranty and free lifetime technical support.

### Hardware

Audio	No
Cables Included	Yes
Daisy-Chain	No
KVM Ports	1
Multi-Monitor	No
PC Interface	USB
PC Video Type	VGA
Rack-Mountable	No

### Performance

Hot-Key Selection	No
-------------------	----

IP Control	No
Maximum Analog Resolutions	1920x1200 @ 60Hz
Maximum Number of Users	1
<b>Connector(s)</b>	
Console Interface(s)	1 - USB Mini-B (5 pin) Female Input
Host Connectors	1 - USB A (4 pin) Male 1 - VGA (15 pin; High Density D-Sub) Male
<b>Software</b>	
OS Compatibility	Windows® 10 (32/64bit), 8 / 8.1 (32/64bit), 7 (32/64), Vista(32/64), XP(32/64) Windows Server® 2012, 2012 R2, 2008 R2 Mac OS® 10.x (Tested up to 10.11) Linux 2.6 - 4.4 (32/64bit) <i>stable only</i>
<b>Indicators</b>	
LED Indicators	1 - Host/Server Keyboard/Mouse USB Link 1 - Host/Server Video (VGA) Link 1 - User Console/USB Link
<b>Power</b>	
Power Source	USB-Powered
<b>Environmental</b>	
Humidity	80% RH
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 70°C (-40°F to 158°F)
<b>Physical Characteristics</b>	
Cable Length	16.4 in [416 mm] 1 x 15in (385mm) USB host cable, 1 x 3in (76mm) VGA host cable, 1 x 6ft (1.8m) USB Console cable
Color	Black
Enclosure Type	Plastic
Product Depth	4.5 in [115 mm]
Product Height	0.6 in [15 mm]
Product Weight	6 oz [170 g]
Product Width	2.9 in [74 mm]
<b>Packaging Information</b>	
Shipping (Package) Weight	12.8 oz [363 g]
<b>What's in the Box</b>	
Included in Package	1 - USB Crash Cart Adpater 1 - USB A to Mini-B Cable 1 - USB Software Key

Gyártó	StarTech
bemeneti csatlakozó	USB-A 2.0