

Philips 345B1C 34" ívelt VA LED monitor (100Hz) fekete



34", 3440x1440, 100Hz, 21:9, 300cd/m², 3000:1, 5ms, USB3.0, HDMI, DisplayPort, fejhallgató kimenet, PIP/PBP, hangszóró, falra szerelhető (VESA), forgatható (swivel), dönthető (tilt), 45W

Cikkszám: 345B1C/00

Ár:

154 230 Ft

Megj.: Monitor LED Philips 345B1C/00, B-line, 34", 3440x1440, 21:9, VA, 5ms, 100Hz, 300nits, HDMI/DP/USB HUB, 5Wx2, Black, 3 Years Display Type: LCD Display Technology: TFT Active Matrix Diagonal Length: 34" Viewable Display Diagonal Length: 34" Type of Matrix: VA Pitch Type: Pixel Pitch Pitch Width: 0.2317 mm Pixel Density: 110 ppi Color Support: 16.7M Maximum Resolution: 3440x1440 Maximum Horizontal Scan Frequency: 160 kHz Minimum Horizontal Scan Frequency: 30 kHz Maximum Vertical Scan Frequency: 100 Hz Minimum Vertical Scan Frequency: 48 Hz Image Brightness: 300 cd/m² Dynamic Contrast Ratio: 80 000 000 : 1 Image Contrast: 3 000 : 1 Image Max. H-View Angle: 178 ° Image Max. V-View Angle: 178 ° Response Time: 5 ms Screen Treatment: Anti-Glare, Hard Coating 2H Image Aspect Ratio: 21:9 Ergonomic Features: Tilt, Height Adjustable, Swivel Display Features: HDCP Ready, SmartImage, White-LED Backlight, SmartControl, PowerSensor, Eco Mode, Flicker-free Technology, Curved Technology, Ultra WQHD, EasyRead, LowBlue Mode Gamut: sRGB 119.3%, NTSC 100%, Adobe RGB 90% Curve Radius: 1500R Multi-Channel Preview: Picture-by-Picture (PBP), Picture-in-Picture (PIP) Speaker Form Factor: Integrated Audio Output Mode: Stereo Output Power per Channel: 5 W DisplayPort: 1 HDMI: 2 (HDMI (Type A)) USB: 1 (USB Type B) USB 3.2 Gen 1: 4 (USB Type A) Headphones: 1 (3.5-mm minijack) Power Device Type: Power Supply Power Device Location: Internal Maximum Input Frequency: 60 Hz Maximum Input Voltage: 240 V Minimum Input Frequency: 50 Hz Minimum Input Voltage: 100 V Power Consumption Operational: 45 W Built-in Devices: USB Hub Cable Included: Power Cable, HDMI Cable, DisplayPort Cable Included Accessories: Stand, Quick Start guide Mounting Capability: Desktop/Wallmount Security Features: Kensington Lock Slot Flat Display Mounting Interface: 100mm Monitor Compliant Standards: VESA DDC/CI, VESA FDMI, TCO, RoHS, Energy Star 7.0 External Color: Black Mean Time Between Failures: 70000 hr Maximum Operating Ambient Temperature: 40 °C Minimum Operating Ambient Temperature: 0 °C Maximum Non-Operating Ambient Temperature: 60 °C Minimum Non-Operating Ambient Temperature: -20 °C Maximum Operating Humidity: 80 % Minimum Operating Humidity: -20 % Max. Altitude Operating: 3658 m Depth (mm): 807 mm Height (mm): 367 mm Width (mm): 110 mm Nominal Weight: 7.62 kg Depth (mm): 807 mm Height (mm): 601 mm Width (mm): 250 mm Weight: 11.32 kg Warranty Products Returnable: Yes Warranty Term (month): 36 month(s) Warranty validation Criteria: Serial Number Pack Weight Brutto (kg): 15.05 kg Pack Weight Netto (kg): 11.32 kg Pieces in pack: 1 Box Weight Brutto (kg): 15.05 kg Retail Packaging Net Weight Carton: 11.32 kg Retail Packaging Net Weight Plastic: 11.32 kg Packs in Box: 1 Package Type: Box