Szanex Bt.

Cégjegyzék szám: 05-06-005646 Adószám: 21302541-2-05 3700 Kazincbarcika, Dózsa Gy. út 24. szanex@szanex.hu (48) 512-880

StarTech 7 portos USB3.0 HUB Industrial

USB3.0 bemenet: 1db, USB3.0 kimenet: 7db

Cikkszám: ST7300USBME

Ár:

81 760 Ft



Engineered to meet the challenges of tough industrial environments, this USB 3.0 hub lets you expand your connectivity options by adding seven external USB 3.0 ports to your computer.

Now you can increase your everyday productivity by gaining powerful and convenient access to your external hard drives, printers, mobile devices and other peripherals.

Reliable performance even in tough industrial environments

Designed for performance and durability, the industrial-grade hub features a rugged, metal housing. Its wide-range 7-48V DC terminal block input gives you the flexibility to power the hub as required, based on your own power input capabilities. Plus, it supports an extended operating temperature range (0°C to 70°C), helping to ensure reliable performance even in the most demanding factory and industrial environments.

The rugged hub also offers ESD protection to each USB port, which can help safeguard your investments by preventing damage to your connected devices.

Secure and versatile installation on DIN rails or surfaces

This wall-mountable USB 3.0 hub can be securely mounted to surfaces, under desks, and in other high traffic areas where there is a concern that USB connections may become unplugged. Plus, it also includes optional DIN rail mounts for use with equipment rack installations.

Supports transfer speeds up to 5Gbps

Compliant with SuperSpeed USB 3.0, this industrial hub supports 5Gbps bandwidth. It's also backward compatible with USB 2.0 and 1.x specifications, simultaneously supporting older USB peripherals or legacy systems that lack USB 3.0 capabilities.

The ST7300USBME is backed by a StarTech.com 2-year warranty and free lifetime technical support.

Bus Type USB 3.0

Chipset ID Genesys Logic - GL3520

Fast-Charge Port(s) Yes

Industry Standards USB Battery Charging Specification Rev. 1.2

USB 3.0 - Backward compatible with USB 2.0 and 1.1

Interface USB 3.0

Ports 7
USB-C Device Port(s) No
USB-C Host Connection No

Performance

Maximum Data Transfer Rate 5 Gbps

MTBF 126,106 Hours
Surge Protection 15kV ESD protection
Type and Rate USB 3.0 - 5 Gbit/s

Connector(s)

Connector Type(s) 7 - USB 3.0 A (9 pin; SuperSpeed) Female

1 - USB 3.0 B (9 pin; SuperSpeed) Female

1 - Terminal Block (2 Wire)

Software

OS Independent; No additional drivers or software required **OS** Compatibility

Special Notes / Requirements

Note If connected to a USB 2.0 host port, performance may be limited

This product is intended for use with terminal block power only - Standard AC adapter

not available

System and Cable Host computer with an available USB 3.0 port

1 - Power (Green)

Requirements **Indicators**

LED Indicators Power

7 ~ 48 DC Input Voltage Power Source Terminal Block

Environmental

Humidity 5%~95% RH (Non-condensing) Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -20°C to 85°C (-4°F to 185°F)

Physical Characteristics

Color Black **Enclosure Type** Steel Form Factor Industrial Product Height 1.8 in [45 mm] Product Length 5.7 in [145 mm] **Product Weight** 11.5 oz [325 g] Product Width 2.1 in [54 mm]

Packaging Information

Shipping (Package) Weight 21.5 oz [610 g]

What's in the Box

1 - 7 Port Industrial USB 3.0 Hub Included in Package

> 1 - USB 3.0 A - B Cable 1 - DIN Rail Mounting Kit 1 - Terminal Block (2 Wire) 1 - Instruction Manual

tömeg	325
Gyártó	StarTech
cikknév kiegészítés	Industrial
portok száma	7
USB3.0	7
USB3.0 bemenet	1
USB3.0 kimenet	7
magasság	45 mm
mélység	54 mm
szélesség	145 mm
szín	fekete