

TP-Link TL-SL1226P PoE switch

LAN (100Mb/s): 24 port, SFP: 2db, energiafelhasználás: 18,32W, fekete
Cikkszám: TL-SL1226P

Ár:
90 810 Ft



Garancia: 5 Év

HARDWARE FEATURES

Interface

- 24× PoE+ 10/100 Mbps RJ45 Ports
- 2× 10/100/1000 Mbps RJ45 Ports
- 2× Combo Gigabit SFP Slots

Network Media

- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)
EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-X MMF, SMF

Fan Quantity

2 Fans

Physical Security Lock

Yes

Power Supply

100-240 VAC, 50/60 Hz

Backup Bandwidth

8.8 Gbps

PoE+ Ports(RJ45)

- Standard: 802.3at/802.3af compliant
- PoE Ports: Port 1 – Port 24
- PoE Power Budget: 250 W

Mac Address Table

8 K

Dimensions (W x D x H)

17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)

Max Power Consumption

18.32 W (220/50 Hz. no PD connected)
294 W (220/50 Hz. with 250 W PD connected)

Max Heat Dissipation

62.47 BTU/h (no PD connected)
1002.54 BTU/h (with 250 W PD connected)

SOFTWARE FEATURES

- Compatible With IEEE 802.3at/af Compliant PDs
- Extend Mode (Up to 250m PoE power supply and data transmission)
- Priority Mode
- Isolation Mode
- PD Detection
- Intelligent Power Supply
- Mac Address Auto-Learning and Auto-Aging
- IEEE802.3x Flow Control

Advanced Features

Transmission MethodStore-And-Forward

OTHERS

Certification

- CE, FCC, RoHS
- TL-SL1226P

Package Contents	• Power Cable • Installation Guide • Two mounting brackets and the fittings
Environment	• Operating Temperature: 0-50 °C (32-122 °F) • Storage Temperature: -40-70 °C (-40-158 °F) • Operating Humidity: 10-90% non-condensing • Storage Humidity: 5-90% non-condensing