

Delock 2 portos displayport 1.2 splitter 4K

DisplayPort bemenet: 1db, DisplayPort kimenet: 2db

Cikkszám: 87691

Ár:

33 420 Ft



This splitter by Delock receives a Displayport signal from a PC or laptop and splits it to two connected displays. Thereby one Displayport connection can be used to operate two Displayport monitors. The outputs are dual-mode capable (DP++), so that HDMI or DVI monitors can be connected with suitable adapters.

Specification

- Connector:
Input:
 - 1 x Displayport 20 pin female
 - 1 x DC 5 V power connectorOutput:
 - 2 x Displayport 20 pin female
- Chipset: STDP4320
- Displayport 1.2a specification
- Active converter, Single / Multi Stream Transport Hub (SST / MST)
- Maximum resolution (depending on the system and the connected hardware):
Displayport 1.1 or 1.2 Single Stream Transport (SST):
 - up to 1920 x 1080 @ 60 Hz (mirror)Displayport 1.2 Multi Stream Transport (MST):
 - up to 2560 x 1440 @ 60 Hz or 3840 x 2160 @ 30 Hz (mirror or extended)
- Displayport output supports Dual Mode DP++
- Supports audio and video signals
- Supports Eyefinity / Single Large Surface (SLS)
- Audio input formats: 7.1 channel up to 192 kHz sample rate
- Metal housing
- Colour: black
- Dimensions (LxWxH): ca. 71 x 61 x 21 mm
- Length: power cable USB Type-A > DC ca. 50 cm

Power supply specification

- Wall power supply
- Input: AC 100 ~ 240 V / 50 ~ 60 Hz / 0.3 A
- Output: 5 V / 1 A
- Ground outside, plus inside
- Dimensions:
 - inside: ø ca. 2.1 mm
 - outside: ø ca. 5.5 mm
 - length: ca. 9 mm

System requirements

- A free Displayport female port

- Displayport cable

Package content

- Displayport Splitter
- USB power cable
- External power supply
- User manual

Gyártó

Delock