

TP-Link TL-SL1218P PoE rack switch

LAN (100Mb/s): 16 port, LAN (1Gb/s): 2 port, SFP: 1db, energiafelhasználás: 172,8W, fekete

Cikkszám: TL-SL1218P

Ár:

80 070 Ft



Garancia: 5 Év

Interface

- 16× PoE+ 10/100 Mbps RJ45 Ports
- 2× 10/100/1000 Mbps RJ45 Ports
- 1× Combo Gigabit SFP Slot
- 10BASE-T: UTP category 3, 4, 5 cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 100BASE-TX: UTP category 5, 5e cable (maximum 100m)

Network Media

- EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-T: UTP category 5, 5e, 6 or above cable (maximum 100m)
- EIA/TIA-568 100Ω STP (maximum 100m)
- 1000BASE-X MMF, SMF

Fan Quantity

2 Fans

Physical Security Lock

Yes

Power Supply

100–240V AC, 50/60 Hz
• Standard: 802.3at/802.3af compliant

PoE+ Ports(RJ45)

- PoE Ports: Ports 1–16
- PoE Power Budget: 150 W

Dimensions (W x D x H)

17.3 × 7.1 × 1.7 in (440 × 180 × 44 mm)

Max Power Consumption

- 12.71 W (220/50Hz. no PD connected)
- 172.8 W (220/50Hz. with 150 W PD connected)

Max Heat Dissipation

- 43.34 BTU/h (no PD connected)
- 589.25 BTU/h (with 150 W PD connected)

PERFORMANCE

Switching Capacity

7.2 Gbps

Packet Forwarding Rate

5.36 Mpps

MAC Address Table

8K

Jumbo Frame

10 KB

SOFTWARE FEATURES

- Compatible With IEEE 802.3at/af Compliant PDs
- Extend Mode (Up to 250m PoE power supply and data transmission)
- Priority Mode
- Isolation Mode
- Mac Address Auto-Learning And Auto-Aging
- IEEE802.3x Flow Control

Advanced Features

Transmission Method

Store-And-Forward

OTHERS

Certification

- CE, FCC, RoHS
- TL-SL1218P

Package Contents

- Power Cable
- Installation Guide

Environment

- Two mounting brackets and the fittings
- Operating Temperature: 0-50 °C (32-122 °F)
- Storage Temperature: -40-70 °C (-40-158 °F)
- Operating Humidity: 10-90% RH non-condensing
- Storage Humidity: 5-90% RH non-condensing

Gyártó

TP-Link