

TP-Link VIGI C450 Turret smart home kültéri IP kamera



5MP, 2,8mm F1.6 1/2,7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 2880x1620, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+;H.264+

Cikkszám: VIGI C450 (2.8MM)

Ár:

41 080 Ft

KAMERA

Képzékelő	1/2.7" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Min. szükséges megvilágítás	0.005 Lux; 0 Lux with IR/white light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Day/Night/Auto/Schedule-Switch

LENS

Type	Fixed Focal Lens
Focal Length	2.8/4 mm
Aperture	2.8 mm: F1.6 4 mm: F1.6 2.8mm:
FOV	Horizontal FOV: 109°, Vertical FOV: 57°, Diagonal FOV: 128°

FOV	4mm:
	Horizontal FOV: 90°, Vertical FOV: 48°, Diagonal FOV: 107°

Lens Mount	M12*P 0.5
	2.8 mm
	Detect: 64 m (209 ft)
	Observe: 27 m (87 ft)
	Recognize: 13 m (42 ft)
	Identify: 6 m (21 ft)

DORI Distance	4 mm
	Detect: 80 m (262 ft)
	Observe: 33 m (109 ft)
	Recognize: 16 m (52 ft)
	Identify: 8 m (26 ft)

VIDEO

Max. Resolution	2880 X 1620
	Frame Rate:
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps

Main Stream	Resolution:
	2880x1620,2688x1520, 2304x1296, 2048x1280, 1920x1080,1280x720

Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Frame Rate:

50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps

Sub-Stream

Resolution:
704x576, 640x480, 352x288, 320x240

Bit Rate Control

Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
CBR, VBR

Video Compression

Main Stream: H.265+/H.265/H.264+/H.264

Sub-Stream: H.265/H.264

H.264 Type

Main Profile/High Profile

H.264+

Main Stream Supported

H.265 Type

Main Profile

H.265+

Main Stream Supported

Video Bit Rate

Main Stream: 256 Kbps to 6 Mbps

Sub-Stream: 64 Kbps to 512 Kbps

ILLUMINATOR

IR LED

Quantity: 2
Range: 30m
Wavelength: 850nm

White LED

Quantity: 2
Range: 30m

Illuminator On/Off Control Auto/Scheduled/Always on/Always off

ANGLE ADJUSTMENT (MANUAL)

Range Pan: 0° to 360°, Tilt: 0° to 85°

IMAGE

Image Settings

Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance, Prevent Overexposure to Infrared Light, HLC Adjustable by Client Software

Image Enhancement

BLC/3D DNR/HLC/SmartIR

Wide Dynamic Range

120 dB

SNR

≥ 52 dB

Image Parameters Switch

Yes

Privacy Mask

Up to 4 Masks

ROI

1 Region

OSD Setting

Yes

HANG

Hangkommunikáció

Two-Way Audio

Hangbemenet

Yes

Hangkimenet

Yes

Hangtömrítés

Yes

Audio Sampling Rate

8KHz

Environment Noise Filtering

Yes

Audio Bit Rate

64 Kbps(G.711 alaw)

HÁLÓZAT

Biztonság

Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication

Szabvány

TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS

Network Storage

NAS (NFS, SMB/ CIFS)

API

Open Network Video Interface (Profile S)

Simultaneous Live View

3 Main Streams & 3 Sub-Streams

Client

VIGI App, VIGI Security Manager, VIGI NVR, Web

Google Chrome® 57 and above

Firefox® 52 and above

Safari® 11 and above

Microsoft® Edge 91 and above

Web Browser

Cloud

Yes

ONVIF

Yes

FIZIKAI KEZELŐFELÜLET

Hálózati csatlakozás 1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE

Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 256 GB
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A

FIGYELMEZTETÉSI ÉS ESEMÉNYKEZELÉSI VEZÉRLÉS

Smart Event	Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection, Loitering Detection
Basic Event	Motion Detection, Video Tampering Detection, Exception (Illegal Login), Scene Change Detection
Alarm Linkage	Memory Card Video Recording, Message Push, Audible Warning, White Light Flashing
Linkage Method	N/A
Output Notification	Message Push

DEEP LEARNING FUNCTION

Multi-Target-Type Detection	Supports Simultaneous Detection and Capture of Human Body and Vehicle
Face Capture	N/A
Face Comparison	N/A

ÁLTALÁNOS

Csomagolás tartalma	VIGI Network Camera Quick Start Guide Mounting Accessories
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Storage Humidity	95% or Less (Non-Condensing)
Operating Humidity	95% or Less (Non-Condensing)
Material	Plastic
Net Weight	0.24 Kg
Gross Weight	0.4 Kg
Power Supply	12V DC ± 5%, 5.5mm Coaxial Power Plug PoE (802.3at, class 0) Maximum: 9 W
Power Consumption	Typical (Day Mode): 1.76 W Typical (Night Mode with IR LED): 3.5 W Typical (Night Mode with White LED): 3.8 W
Product Dimensions (L x W x H)	Φ123x84 mm
Certifications	CE, NTRA, VCCI, KC, BSMI, FCC, IC

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	5MP
látószög	128°
smart home	Van
videó felbontása	2880x1620
Gyártó	TP-Link
beépített mikrofon	Van
csatlakozó	Ethernet (100Mb/s)

döntési szög	85
éjszakai mód	Van
érzékelő típusa	2,8mm F1.6 1/2,7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	mennyezetre rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	30
szín	fehér