

Brother DCP-L2622DW multifunkciós lézernyomtató



másoló, szkennер, A4, duplex, 1200x1200 DPI, USB2.0, Wi-Fi, 256MB, fekete, 10,1kg

Cikkszám: DCPL2622DWYJ1

Ár:

92 230 Ft

General Specifications

Printer Type

- Laser
- Electrophotographic Laser Printer
- (DCP-L2600D/DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

Print Method

128 MB

Memory Capacity Standard

- (DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)

256 MB

- (DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

16 characters x 2 lines

Liquid Crystal Display (LCD)

- (DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)

2.7 in. (67.5 mm) TFT Colour touchscreen LCD *1

- (MFC-L2922DW)

3.5 in. (87.6 mm) TFT Colour touchscreen LCD *1

Power Source

- 220 V to 240 V AC 50/60 Hz

Peak

- Approximately 920 W

Printing *2

- Approximately 470 W at 25°C

Printing

- Approximately 270 W at 25°C

(Quiet Mode) *2

Copying *2

Copying
(Quiet Mode) *2

Ready *2

Sleep *2

Deep Sleep *2

Power Off *2 *3 *4

Dimensions

(Typical outline view)

(DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE)



(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)



(MFC-L2922DW)



- (DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

Approximately 480 W at 25°C

- (DCP-L2600D/DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)

Approximately 490 W at 25°C

- Approximately 280 W at 25°C

- Approximately 43 W at 25°C

- Approximately 4.1 W

- (DCP-L2600D)

Approximately 0.5 W

- (DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

Approximately 0.6 W

- (DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)

Approximately 0.7 W

- Approximately 0.08 W

Unit: mm

- (DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE)

* : 410

** : 272

*** : 399

- (DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)

* : 410

** : 319

*** : 399

- (MFC-L2922DW)

* : 410

** : 319

*** : 421

- (DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWE)

10.1 kg

Weight (with supplies)			(DCP-L2627DWXL)
			11.2 kg
			(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW)
			11.4 kg
			(MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)
			11.6 kg
			(MFC-L2922DW)
			11.8 kg
			(MFC-L2827DWXL)
			12.7 kg

Noise Level	Sound Pressure *5	Printing	• LpAm = 49 dB (A)
		Printing	• LpAm = 44 dB (A)
		(Quiet Mode)	
	Sound Power	Ready	• LpAm = 30 dB(A)
		Printing *5	• LWAc = 6.63 B (A)
		Printing	• LWAc = 6.12 B (A)
Temperature	Operating	(Quiet Mode)	
		Ready	• LWAc = Inaudible
			• From 10°C to 32.5°C
Humidity	Storage		• From 0°C to 40°C
			• 20% to 80% (without condensation)
			• 35% to 85% (without condensation)
Automatic Document Feeder (ADF)			• Up to 50 sheets

(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)	For best results we recommend:
	- Temperature: 20°C to 30°C - Humidity: 50% to 70% - Paper: 80 g/m2

*1
Measured diagonally.

*2
USB connections to a computer.

*3
Measured according to IEC 62301 Edition 2.0.

*4
Power consumption varies slightly depending on the usage environment.

*5
Measured in accordance with the method described in ISO 7779.

Document Size Specification	
ADF Width *1	105 mm to 215.9 mm

Document Size	ADF Length *1	• 147.3 mm to 355.6 mm
	Scanner Glass Width	• Maximum 215.9 mm
	Scanner Glass Length	• Maximum 300 mm

*1

ADF models only

Print Media Specifications

Paper Input	Paper Tray (Standard)	Paper Type	• Plain Paper, Thin Paper, Recycled Paper, Thick Paper
		Paper Size	• A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, 16K (195x270 mm), A4 Short (270mm Paper)
		Paper Weight	• 60 to 163 g/m2 *1
		Maximum Paper Capacity	• Up to 250 sheets of 80 g/m2 Plain Paper
	Manual Feed Slot	Paper Type	• Plain Paper, Thin Paper, Thick Paper, Thicker Paper, Recycled Paper, Bond, Label, Envelope, Env.Thin, Env.Thick
			• Width: 76.2 to 215.9 mm
		Paper Size	• Length: 127 to 355.6 mm
			• Envelope: COM-10, DL, C5, Monarch
		Paper Weight	• 60 to 230 g/m2
		Maximum Paper Capacity	• One sheet at a time
Paper Output *2	Face Down Output Tray		• Up to 120 Sheets (face down delivery to the face down output paper tray) *3
	Face Up Output Tray		• One sheet (face up delivery to the face up output tray)
2-sided	Automatic 2-sided Printing	Paper Type	• Plain Paper, Thin Paper, Recycled Paper
		Paper Size	• A4
		Paper Weight	• 60 to 105 g/m2

*1

For paper of 105 g/m2 and above, open the back cover to use the face up output tray.

*2

For labels, we recommend removing the printed sheets from the output paper tray immediately after they exit the machine to avoid the possibility of smudging.

*3

Calculated with 80 g/m2 in a temperate, non humid environment. Actual output tray capacity may vary depending on environmental conditions.

Fax Specifications

NOTE

This feature is available for MFC models.

Compatibility	• ITU-T Super Group 3
Coding System	• MH / MR / MMR / JBIG
Modem Speed	• 33,600 bps (with Automatic Fallback)

2-sided Print Receiving	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Yes
Automatic 2-sided Sending	• (MFC-L2922DW) Yes (from the ADF)
Scanning Width	• Maximum 208 mm
Printing Width	• Maximum 207.4 mm
Greyscale	• 8 bit / 256 levels
Horizontal	• 203 dpi • Standard: 98 dpi
Resolution Vertical	• Fine: 196 dpi • Super fine: 392 dpi • Photo: 196 dpi
Address Book	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) 200 Locations
Shortcut	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW) 10 locations
Groups	• Up to 20 • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Broadcasting	260 Locations • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) 250 Locations
Automatic Redial	• 3 times at 5-minute intervals • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Memory Transmission	Up to 400 pages *1 • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Up to 500 pages *1 • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Out of Paper Reception	Up to 400 pages *1 • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Up to 500 pages *1

*1

‘Pages’ refers to the ‘ITU-T TestChart Document No.1’ (a typical business letter, Standard resolution, JBIG code).

Copy Specification

Copy Width	• Maximum 210 mm
Automatic 2-sided Copy	• (MFC-L2922DW) Yes (from the ADF)
Sort Copy	• Yes

Stack Copy	Up to 99 pages
Resolution	Maximum 600 x 600 dpi
First Copy Out Time *1	Less than 10 seconds at 23°C

*1

From Ready Mode and standard tray.

Scanner Specifications

Colour / Black	Yes / Yes
TWAIN Compliant	Yes (Windows 10 / Windows 11)
WIA Compliant	Yes (Windows 10 / Windows 11)
AirPrint Compliant	(DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Yes (macOS v11, v12, v13)
Colour Depth	30 bit colour Processing (Input) 24 bit colour Processing (Output)
Grey Scale	10 bit colour Processing (Input) 8 bit colour Processing (Output) Up to 19200 x 19200 dpi (interpolated)
Resolution *2	- Up to 1200 x 1200 dpi (from Scanner Glass) - Up to 600 x 600 dpi (from the ADF) *1
Scanning Width	Maximum 210 mm
Automatic 2-sided Scanning	(MFC-L2922DW) Yes (from the ADF)

*1

ADF models only

*2

Maximum 1200 × 1200 dpi scanning with the WIA driver in Windows 10 and Windows 11 (resolution up to 19200 × 19200 dpi can be selected by using the scanner utility)

Printer Specifications

Automatic 2-sided Print	Yes
Emulation	(DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) PCL6, BR-Script3, PDF Version 1.7
Resolution	- Up to 1200 x 1200 dpi (DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

Print Speed *1 *2	1-sided Print *3	Up to 32 pages/minute (A4 size)
		Up to 34 pages/minute (Letter size)
	2-sided Print	• (DCP-L2600D/DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)
		• Up to 16 pages/minute (Up to 8 sheets/minute) (A4 size)
First Print Time *4		Up to 34 pages/minute (A4 size)
		Up to 36 pages/minute (Letter size)
		Up to 17 pages/minute (Up to 8.5 sheets/minute) (Letter size)
		• Less than 8.5 seconds at 23°C

*1
The print speed may change depending on the type of document you print.

*2
The print speed may be slower when the machine is connected by wireless LAN.

*3
These print speeds are for 1-sided printing and measured in accordance with the ISO/IEC 24734 standard.

*4
From Ready mode and standard tray.

Interface Specifications

USB *1 *2	• Hi-Speed USB 2.0
	Use a USB 2.0 interface cable that is no more than 2 metres long.
LAN	• (DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)
	10Base-T/100Base-TX *3
Wireless LAN	• (DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2660DW/DCP-L2665DW/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)
	IEEE 802.11a/b/g/n (Infrastructure Mode)
NFC	IEEE 802.11a/g/n (Wi-Fi Direct®)
	• (MFC-L2922DW)
	Yes

*1
Your machine has a USB 2.0 Hi-Speed interface. The machine can also be connected to a computer that has a USB 1.1 interface.

*2
Third party USB hub devices are not supported.

*3
Use a straight-through Category 5 (or greater) twisted-pair cable.

Supported Protocols and Security Features
Supported protocols and security features may differ depending the models.

Ethernet
10Base-T/100Base-TX

Wireless LAN (2.4GHz)

IEEE 802.11b/g/n (Infrastructure Mode), IEEE 802.11g/n (Wi-Fi Direct)

Wireless LAN (5GHz)

IEEE 802.11a/n (Infrastructure Mode), IEEE 802.11a/n (Wi-Fi Direct)

Protocols (IPv4)

ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, POP3, SMTP Client, IPP/IPPS, FTP Client and Server,CIFS Client, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), Syslog, SMTP Client,IMAP4,LDAP

Protocols (IPv6)

NDP, RA, DNS resolver, mDNS, LLNMR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, Web Services (Print/Scan), Syslog, SMTP Client,IMAP4,LDAP

Network Security (Wired)

APOP*, SMTP-AUTH, SSL/TLS (SMTP, HTTP, IPP, POP3, IMAP4,FTP)*, SNMP v3, 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), OAuth(SMTP, POP3, IMAP4), Kerberos

*When Internet FAX is downloaded.

Network Security (Wireless)

APOP*, SMTP-AUTH, SSL/TLS (SMTP, HTTP, IPP, POP3, IMAP4,FTP)*, SNMP v3, 802.1x (EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), OAuth(SMTP, POP3, IMAP4), Kerberos

*When Internet FAX is downloaded.

Wireless Network Security

WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES) (Wi-Fi Direct supports WPA2-PSK (AES) only)

Wireless Certification

Wi-Fi Certification Mark License (WPA3™ - Enterprise, Personal), Wi-Fi Protected Setup™ (WPS) Identifier Mark License, Wi-Fi CERTIFIED™ Wi-Fi Direct

Computer Requirements Specifications

Supported Operating Systems And Software Functions

For the latest supported OS, go to your model's Supported OS page at support.brother.com/os.

Computer Platform & Operating System Version	PC Interface		Processor	Hard Disk Space to Install *1	
	USB *2	Wired LAN	Wireless LAN	For Drivers	For Applications (including Drivers)
Windows 10 Home / 10 Pro / 10 Education / 10 Enterprise *4 *5	Printing			32 bit (x86) or 64 bit (x64) processor	80 MB 1.8 GB
Windows 11 Home / 11 Pro / 11 Education / 11 Enterprise *4 *5	PC Fax *3			64 bit (x64) processor	
Windows Server 2012	Scanning				
Windows Server 2012 R2					
Windows Server 2016	Printing	Printing		64 bit (x64) processor	80 MB 80 MB
Windows Server 2019	Scanning				
Windows Server 2022					
macOS v11 *6	Printing				
macOS v12 *6	PC-Fax (Send) *3			64 bit processor	N/A 500 MB

macOS v13 *6		Scanning			
Chrome OS		Printing	N/A	N/A	N/A
		Scanning			
*1					
An Internet connection is required to install the software if the installation disc is not supplied.					
*2					
Third party USB ports are not supported.					
*3					
PC-Fax supports black and white only.					
*4					
For WIA, 1200x1200 resolution. Brother Scanner Utility enables to enhance up to 19200 x 19200 dpi.					
*5					
PaperPort™ 14SE supports Windows 10 and Windows 11.					
*6					
macOS DisclaimerAirPrint capable: Printing, scanning, or PC faxing(Send) via macOS requires the use of AirPrint. Mac drivers are not provided for this machine.					
General Specifications					
Printer Type		• Laser			
Print Method		• Electrophotographic Laser Printer • (DCP-L2600D/DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)			
Memory Capacity	Standard	128 MB			
		• (DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)			
		256 MB			
Liquid Crystal Display (LCD)		• (DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)			
		16 characters x 2 lines			
		• (DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)			
Power Source		2.7 in. (67.5 mm) TFT Colour touchscreen LCD *1			
		• (MFC-L2922DW)			
		3.5 in. (87.6 mm) TFT Colour touchscreen LCD *1			
Power Source		• 220 V to 240 V AC 50/60 Hz			
		• Approximately 920 W			
		• Approximately 470 W at 25°C			
		• Approximately 270 W at 25°C			
	Peak				
	Printing *2				
	Printing				
	(Quiet Mode) *2				

Power Consumption (Average)	Copying *2	(DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW) Approximately 480 W at 25°C
	Copying (Quiet Mode) *2	(DCP-L2600D/DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Approximately 490 W at 25°C
	Ready *2	Approximately 280 W at 25°C
	Sleep *2	- Approximately 43 W at 25°C - Approximately 4.1 W (DCP-L2600D) Approximately 0.5 W
	Deep Sleep *2	(DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW) Approximately 0.6 W (DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Approximately 0.7 W - Approximately 0.08 W
Power Off *2 *3 *4		Unit: mm
Dimensions (Typical outline view)	(DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE)	(DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE) * : 410 ** : 272 *** : 399
	(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)	(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW) * : 410 ** : 319 *** : 399
	(MFC-L2922DW)	(MFC-L2922DW) * : 410 ** : 319 *** : 421
		(DCP-L2600D/DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWE) 10.1 kg
		(DCP-L2627DWXL)

Weight (with supplies)			11.2 kg	• (DCP-L2640DN/DCP-L2660DW/DCP-L2665DW)
			11.4 kg	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW)
			11.6 kg	• (MFC-L2922DW)
			11.8 kg	• (MFC-L2827DWXL)
			12.7 kg	
Noise Level	Sound Pressure *5	Printing	• LpAm = 49 dB (A)	
		Printing (Quiet Mode)	• LpAm = 44 dB (A)	
		Ready	• LpAm = 30 dB(A)	
		Printing *5	• LWAc = 6.63 B (A)	
		Printing (Quiet Mode)	• LWAc = 6.12 B (A)	
Temperature	Sound Power	Ready	• LWAc = Inaudible	
		Operating	• From 10°C to 32.5°C	
		Storage	• From 0°C to 40°C	
Humidity		Operating	• 20% to 80% (without condensation)	
		Storage	• 35% to 85% (without condensation)	
Automatic Document Feeder (ADF)			• Up to 50 sheets	
(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)			For best results we recommend:	
			• Temperature: 20°C to 30°C	
			• Humidity: 50% to 70%	
			• Paper: 80 g/m2	

*1
Measured diagonally.

*2
USB connections to a computer.

*3
Measured according to IEC 62301 Edition 2.0.

*4
Power consumption varies slightly depending on the usage environment.

*5
Measured in accordance with the method described in ISO 7779.

Document Size Specification		
ADF Width *1		• 105 mm to 215.9 mm
ADF Length *1		• 147.3 mm to 355.6 mm

Document Size	
Scanner Glass Width	Maximum 215.9 mm
Scanner Glass Length	Maximum 300 mm

*1

ADF models only

Print Media Specifications

Paper Input	Paper Tray (Standard)	Paper Type	Plain Paper, Thin Paper, Recycled Paper, Thick Paper
		Paper Size	A4, Letter, B5 (JIS), B5 (ISO), A5, A5 (Long Edge), B6 (JIS), A6, Executive, 16K (195x270 mm), A4 Short (270mm Paper)
		Paper Weight	60 to 163 g/m2 *1
		Maximum Paper Capacity	Up to 250 sheets of 80 g/m2 Plain Paper
	Manual Feed Slot	Paper Type	Plain Paper, Thin Paper, Thick Paper, Thicker Paper, Recycled Paper, Bond, Label, Envelope, Env.Thin, Env.Thick
			Width: 76.2 to 215.9 mm
		Paper Size	Length: 127 to 355.6 mm
			Envelope: COM-10, DL, C5, Monarch
		Paper Weight	60 to 230 g/m2
		Maximum Paper Capacity	One sheet at a time
	Paper Output *2	Face Down Output Tray	Up to 120 Sheets (face down delivery to the face down output paper tray) *3
		Face Up Output Tray	One sheet (face up delivery to the face up output tray)
2-sided	Automatic 2-sided Printing	Paper Type	Plain Paper, Thin Paper, Recycled Paper
		Paper Size	A4
		Paper Weight	60 to 105 g/m2

*1

For paper of 105 g/m2 and above, open the back cover to use the face up output tray.

*2

For labels, we recommend removing the printed sheets from the output paper tray immediately after they exit the machine to avoid the possibility of smudging.

*3

Calculated with 80 g/m2 in a temperate, non humid environment. Actual output tray capacity may vary depending on environmental conditions.

Fax Specifications

NOTE

This feature is available for MFC models.

Compatibility	ITU-T Super Group 3
Coding System	MH / MR / MMR / JBIG
Modem Speed	33,600 bps (with Automatic Fallback)
Supported Protocols	(MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-

Z-sided Print Receiving	L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)
	Yes
Automatic 2-sided Sending	• (MFC-L2922DW) Yes (from the ADF)
Scanning Width	• Maximum 208 mm
Printing Width	• Maximum 207.4 mm
Greyscale	• 8 bit / 256 levels
Horizontal	• 203 dpi • Standard: 98 dpi
Resolution Vertical	• Fine: 196 dpi • Super fine: 392 dpi • Photo: 196 dpi
Address Book	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) 200 Locations
Shortcut	• (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW) 10 locations
Groups	• Up to 20 • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Broadcasting	260 Locations • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) 250 Locations
Automatic Redial	• 3 times at 5-minute intervals • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Memory Transmission	Up to 400 pages *1 • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Up to 500 pages *1 • (MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)
Out of Paper Reception	Up to 400 pages *1 • (MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Up to 500 pages *1
*1	
'Pages' refers to the 'ITU-T TestChart Document No.1' (a typical business letter, Standard resolution, JBIG code).	
Copy Specification	
Copy Width	• Maximum 210 mm • (MFC-L2922DW)
Automatic 2-sided Copy	Yes (from the ADF)
Sort Copy	• Yes

Stack Copy	Up to 99 pages
Resolution	Maximum 600 x 600 dpi
First Copy Out Time *1	Less than 10 seconds at 23°C

*1

From Ready Mode and standard tray.

Scanner Specifications

Colour / Black	Yes / Yes
TWAIN Compliant	Yes (Windows 10 / Windows 11)
WIA Compliant	Yes (Windows 10 / Windows 11)
AirPrint Compliant	(DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) Yes (macOS v11, v12, v13)
Colour Depth	30 bit colour Processing (Input) 24 bit colour Processing (Output)
Grey Scale	10 bit colour Processing (Input) 8 bit colour Processing (Output) - Up to 19200 x 19200 dpi (interpolated)
Resolution *2	- Up to 1200 x 1200 dpi (from Scanner Glass) - Up to 600 x 600 dpi (from the ADF) *1
Scanning Width	Maximum 210 mm
Automatic 2-sided Scanning	(MFC-L2922DW) Yes (from the ADF)

*1

ADF models only

*2

Maximum 1200 × 1200 dpi scanning with the WIA driver in Windows 10 and Windows 11 (resolution up to 19200 × 19200 dpi can be selected by using the scanner utility)

Printer Specifications

Automatic 2-sided Print	Yes
Emulation	(DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) PCL6, BR-Script3, PDF Version 1.7
Resolution	- Up to 1200 x 1200 dpi (DCP-L2620DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW)

Print Speed *1 *2	1-sided Print *3	Up to 32 pages/minute (A4 size)
		Up to 34 pages/minute (Letter size)
	2-sided Print	• (DCP-L2600D/DCP-L2622DW/DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW)
		Up to 34 pages/minute (A4 size) Up to 36 pages/minute (Letter size)
First Print Time *4		• Up to 16 pages/minute (Up to 8 sheets/minute) (A4 size) Up to 17 pages/minute (Up to 8.5 sheets/minute) (Letter size)
		• Less than 8.5 seconds at 23°C

*1

The print speed may change depending on the type of document you print.

*2

The print speed may be slower when the machine is connected by wireless LAN.

*3

These print speeds are for 1-sided printing and measured in accordance with the ISO/IEC 24734 standard.

*4

From Ready mode and standard tray.

Interface Specifications

USB *1 *2	Hi-Speed USB 2.0 Use a USB 2.0 interface cable that is no more than 2 metres long.
LAN	(DCP-L2640DN/DCP-L2660DW/DCP-L2665DW/MFC-L2802DN/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) 10Base-T/100Base-TX *3
Wireless LAN	(DCP-L2620DW/DCP-L2622DW/DCP-L2627DW/DCP-L2627DWXL/DCP-L2627DWE/DCP-L2660DW/DCP-L2665DW/MFC-L2800DW/MFC-L2802DW/MFC-L2827DWXL/MFC-L2827DW/MFC-L2835DW/MFC-L2860DWE/MFC-L2860DW/MFC-L2862DW/MFC-L2922DW) IEEE 802.11a/b/g/n (Infrastructure Mode) IEEE 802.11a/g/n (Wi-Fi Direct®)
NFC	(MFC-L2922DW) Yes

*1

Your machine has a USB 2.0 Hi-Speed interface. The machine can also be connected to a computer that has a USB 1.1 interface.

*2

Third party USB hub devices are not supported.

*3

Use a straight-through Category 5 (or greater) twisted-pair cable.

Supported Protocols and Security Features

Supported protocols and security features may differ depending the models.

Ethernet

10Base-T/100Base-TX

Wireless LAN (2.4GHz)

IEEE 802.11b/g/n (Infrastructure Mode), IEEE 802.11g/n (Wi-Fi Direct)

Wireless LAN (5GHz)

IEEE 802.11a/n (Infrastructure Mode), IEEE 802.11a/n (Wi-Fi Direct)

Protocols (IPv4)

ARP, RARP, BOOTP, DHCP, APIPA(Auto IP), WINS/NetBIOS name resolution, DNS Resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, POP3, SMTP Client, IPP/IPPS, FTP Client and Server,CIFS Client, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMP, Web Services (Print/Scan), Syslog, SMTP Client,IMAP4,LDAP

Protocols (IPv6)

NDP, RA, DNS resolver, mDNS, LLMNR responder, LPR/LPD, Custom Raw Port/Port9100, IPP/IPPS, POP3, SMTP Client, FTP Client and Server, CIFS Client, SNMPv1/v2c/v3, HTTP/HTTPS server, TFTP client and server, ICMPv6, Web Services (Print/Scan), Syslog, SMTP Client,IMAP4,LDAP

Network Security (Wired)

APOP*, SMTP-AUTH, SSL/TLS (SMTP, HTTP, IPP, POP3, IMAP4,FTP)*, SNMP v3, 802.1x (EAP-MD5, EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), OAuth(SMTP, POP3, IMAP4), Kerberos

*When Internet FAX is downloaded.

Network Security (Wireless)

APOP*, SMTP-AUTH, SSL/TLS (SMTP, HTTP, IPP, POP3, IMAP4,FTP)*, SNMP v3, 802.1x (EAP-FAST, PEAP, EAP-TLS, EAP-TTLS), OAuth(SMTP, POP3, IMAP4), Kerberos

*When Internet FAX is downloaded.

Wireless Network Security

WEP 64/128 bit, WPA-PSK (TKIP/AES), WPA2-PSK (TKIP/AES), WPA3-SAE (AES) (Wi-Fi Direct supports WPA2-PSK (AES) only)

Wireless Certification

Wi-Fi Certification Mark License (WPA3™ - Enterprise, Personal), Wi-Fi Protected Setup™ (WPS) Identifier Mark License, Wi-Fi CERTIFIED™ Wi-Fi Direct

Computer Requirements Specifications

Supported Operating Systems And Software Functions

For the latest supported OS, go to your model's Supported OS page at support.brother.com/os.

Computer Platform & Operating System Version	PC Interface			Processor	Hard Disk Space to Install *1	
	USB *2	Wired LAN	Wireless LAN		For Drivers	For Applications (including Drivers)
Windows 10 Home / 10 Pro / 10 Education / 10 Enterprise *4 *5	Printing			32 bit (x86) or 64 bit (x64) processor	80 MB	1.8 GB
Windows 11 Home / 11 Pro / 11 Education / 11 Enterprise *4 *5	PC Fax *3			64 bit (x64) processor		
Windows Server 2012	Scanning					
Windows Server 2012 R2						
Windows Server 2016	Printing	Printing		64 bit (x64) processor	80 MB	80 MB
Windows Server 2019	Scanning					
Windows Server 2022						
macOS v11 *6	Printing					
macOS v12 *6	PC-Fax (Send) *3			64 bit processor	N/A	500 MB

macOS v13	*6	Scanning			
Chrome OS		Printing	N/A	N/A	N/A
		Scanning			
*1					
An Internet connection is required to install the software if the installation disc is not supplied.					
*2					
Third party USB ports are not supported.					
*3					
PC-Fax supports black and white only.					
*4					
For WIA, 1200x1200 resolution. Brother Scanner Utility enables to enhance up to 19200 x 19200 dpi.					
*5					
PaperPort™ 14SE supports Windows 10 and Windows 11.					
*6					
macOS DisclaimerAirPrint capable: Printing, scanning, or PC faxing(Send) via macOS requires the use of AirPrint. Mac drivers are not provided for this machine.					

duplex	Van
duplex típusa	automata
max nyomtatási papírformátum	A4
multifunkciós	Van
nyomtató típusa	lézernyomtató
színes	Nincs
szkenner	Van
Wi-Fi	Van
Gyártó	Brother
kijelző típusa	LCD
másoló	Van
memória mérete	256
monokróm nyomtatási sebesség (lap/perc)	34
nyomtatási felbontás	1200x1200
tömeg	10.1 kg
USB2.0	Van
szín	fekete