

TP-Link VIGI C355 smart home kültéri IP kamera IP67

5MP, 4mm F1.6 1/2.7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 2880x1620, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+;H.264+, 525g

Cikkszám: VIGI C355 (4MM)

Ár:

113 510 Ft



CAMERA

Image Sensor	1/2.7" Progressive Scan CMOS
Day/Night Switch	Unified/ Scheduled/ Auto
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	0.005 Lux; 0 Lux with IR/White light
Day/Night Mechanism	IR Cut Filter

LENS

Type	Fixed Focal Lens
Focal Length	2.8/4/6 mm
Aperture	F1.6
	• 2.8 mm:
	Horizontal FOV: 111.4°, Vertical FOV: 58.8°, Diagonal FOV: 134°

FOV

• 4 mm:
Horizontal FOV: 88°, Vertical FOV: 46°, Diagonal FOV: 105.4°

Lens Mount

• 6 mm:
Horizontal FOV: 57.3°, Vertical FOV: 31.3°, Diagonal FOV: 67.2°
M12*P 0.5
• 2.8 mm
Detect: 64 m (210 ft)
Observe: 27 m (89 ft)
Recognize: 13 m (43 ft)
Identify: 6 m (20 ft)

DORI Distance

• 4 mm
Detect: 80 m (262 ft)
Observe: 33 m (108 ft)
Recognize: 16 m (52 ft)
Identify: 8 m (26 ft)

ANGLE ADJUSTMENT (MANUAL)

RangePan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°

ILLUMINATOR

IR LED	• Quantity: 2
	• Range: 30m
White LED	• Wavelength: 850nm
	• Quantity: 2
Illuminator On/Off Control	• Range: 30m
	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2880 X 1620
	• Frame Rate:
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Main Stream	• Resolution:
	2880x1620,2688x1520, 2304x1296, 2048x1280, 1920x1080, 1280x720
	Note:
	• If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
	Frame Rate:
	50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
	60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Sub-Stream	Resolution:
	704x576,640x480, 352x288, 320x240
	Note:
Bit Rate Control	• If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
	CBR, VBR
	• Main Stream: H.265+/H.265/H.264+/H.264
Video Compression	• Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile*
H.265+	Main Stream Supported*
Video Bit Rate	• Main Stream: 256 Kbps to 6 Mbps
	• Sub-Stream: 64 Kbps to 512 Kbps
IMAGE	
	• Mirror
	• Brightness
	• Contrast
	• Saturation
	• Sharpness
	• Exposure
Image Settings	• WDR
	• White Balance
	• Prevent Overexposure to Infrared Light
Image Enhancement	• HLC Adjustable by Client Software
	BLC/3D DNR/HLC/SmartIR
	120 dB
Wide Dynamic Range	
SNR	Note: When People & Vehicle Analytics is enabled, only DWDR is supported.
	? 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	Two-Way Audio
Audio Input	Yes
Audio Output	Yes
Audio Compression	Yes
Audio Sampling Rate	8KHz

Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI, VIGI VMS • Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Web Browser	
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	
Smart Event	• Human & Vehicle Classification • Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • Loitering Detection • Smart Frame • People Detection • Vehicle Detection • Motion Detection
Basic Event	• Video Tampering Detection • Exception (Illegal Login) • Scene Change Detection • Memory Card Video Recording
Alarm Linkage	• Message Push • Audible Warning • White Light Flashing
Linkage Method	N/A
Output Notification	Message Push
DEEP LEARNING FUNCTION	
People & Vehicle Analytics	Search and filter to people or vehicle of interest based on many different attributes, making post-event search faster and easier.
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 256 GB**
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A
GENERAL	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing) • VIGI Network Camera • Quick Start Guide • Waterproof Cable Attachments • Mounting Accessories
Package Contents	
Material	Metal
Net Weight	0.525 Kg
Power Supply	• 12V DC ± 5%, Max. 9.7 W, 5.5 mm Coaxial Power Plug • PoE: 802.3af/at, class 0, Max. 10.7 W

Protection

Product Dimensions (L x W x H)

Certifications

IP67

74 × 184 × 74 mm

CE, NTRA, VCCI, KC, BSMI, FCC, IC

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	5MP
látószög	105°
smart home	Van
tömeg	525
videó felbontása	2880x1620
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
döntési szög	90
éjszakai mód	Van
érzékelő típusa	4mm F1.6 1/2.7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	falra és mennyezetre rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	30
szín	fehér