

TP-Link VIGI C485 Turret smart home kültéri IP kamera
IP67



8MP, 2,8mm F1.6 1/2,7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 3840x2160, 25fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér, H.265+;H.264+, 480g

Cikkszám: VIGI C485 (2.8MM)

Ár:

130 650 Ft

Garancia: 3 Év

CAMERA

Image Sensor 1/2.7" Progressive Scan CMOS
Day/Night Switch Unified/ Scheduled/ Auto
Shutter Speed 1/3 to 1/10000 s
Slow Shutter Yes
Minimum Illumination 0.005 Lux; 0 Lux with IR/White light
Day/Night Mechanism IR Cut Filter

LENS

Type Fixed Focal Lens
Focal Length 2.8/4 mm
Aperture F1.6
• 2.8 mm:
Horizontal FOV: 111.4°, Vertical FOV: 58.8°, Diagonal FOV: 134°

FOV

• 4 mm:
Horizontal FOV: 91.5°, Vertical FOV: 46.1°, Diagonal FOV: 109.6°

Lens Mount M12*P 0.5
• 2.8 mm
Detect: 85 m (278 ft)
Observe: 35 m (116 ft)
Recognize: 17 m (56 ft)
Identify: 8 m (28 ft)

DORI Distance

• 4 mm
Detect: 107 m (350 ft)
Observe: 44 m (146 ft)
Recognize: 21 m (70 ft)
Identify: 11 m (35 ft)

ANGLE ADJUSTMENT (MANUAL)

Range Pan: 0° to 360°, Tilt: 0° to 85°, Rotation: 0° to 360°

ILLUMINATOR

IR LED Quantity: 4
Range: 30m
Wavelength: 850nm

White LED Quantity: 4
Range: 30m

Illuminator On/Off Control Auto/Scheduled/Always on/Always off

VIDEO

Max. Resolution	3840 X 2160 Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Main Stream	- Resolution: 3840x2160, 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 Note: - If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. - If 120dB is turned on, the frame rate can only support up to 20fps. Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps
Sub-Stream	Resolution: 704x576,640x480, 352x288, 320x240 Note: - If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. - If 120dB is turned on, the frame rate can only support up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264
H.264 Type	High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile*
H.265+	Main Stream Supported*
Video Bit Rate	Main Stream: 256 Kbps to 6 Mbps Sub-Stream: 64 Kbps to 512 Kbps
IMAGE	
Image Settings	- Mirror - Brightness - Contrast - Saturation - Sharpness - Exposure - WDR - White Balance - Prevent Overexposure to Infrared Light - HLC Adjustable by Client Software
Image Enhancement	BLC/3D DNR/HLC/SmartIR 120 dB
Wide Dynamic Range	Note: When People & Vehicle Analytics is enabled, only DWDR is supported.
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
AUDIO	
Audio Communication	Two-Way Audio
Audio Input	Yes
Audio Output	Yes
Audio Compression	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
NETWORK	
Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS

ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI, VIGI VMS Google Chrome® 57 and above
Web Browser	Firefox® 52 and above Safari® 11 and above Microsoft® Edge 91 and above
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
ALARM AND EVENT MANAGEMENT	
	• Human & Vehicle Classification • Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • Loitering Detection • Smart Frame • People Detection • Vehicle Detection • Motion Detection
Smart Event	• Video Tampering Detection • Exception (Illegal Login) • Scene Change Detection • Memory Card Video Recording
Basic Event	• Message Push • Audible Warning • White Light Flashing
Alarm Linkage	
Linkage Method	N/A
Output Notification	Message Push
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, up to 256 GB**
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A
GENERAL	
Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Contents	VIGI Network Camera Quick Start Guide Waterproof Cable Attachments Mounting Accessories
Material	Metal
Net Weight	0.48 Kg
Power Supply	12V DC ± 5%, Max. 11.5 W, 5.5 mm Coaxial Power Plug PoE: 802.3af/at, class 0, Max. 12.5 W
Protection	IP67
Product Dimensions (L x W x H)	111 × 111 × 83.7 mm
Certifications	CE, NTRA, VCCI, KC, BSMI, FCC, IC

alakfelismerés	Van
beépített hangszóró	mono

érzékelő felbontása	8MP
látószög	134°
smart home	Van
tömeg	480
videó felbontása	3840x2160
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
döntési szög	85
éjszakai mód	Van
érzékelő típusa	2,8mm F1.6 1/2,7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	falra rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	25
szín	fehér