

Zyxel GS1350-6HP CCTV PoE switch 60W

LAN (1Gb/s): 5 port, SFP: 1db, menedzselhető

Cikkszám: GS1350-6HP-EU0101F

Ár:

81 230 Ft



Garancia: 5 Év

Models				
	GS1350-6HP	GS1350-12HP	GS1350-18HP	GS1350-26HP
Model				
Product name	5-port GbE Smart Managed PoE Switch with GbE Uplink	8-port GbE Smart Managed PoE Switch with GbE Uplink	16-port GbE Smart Managed PoE Switch with GbE Uplink	24-port GbE Smart Managed PoE Switch with GbE Uplink
Switch class	Smart Managed	Smart Managed	Smart Managed	Smart Managed
Port Density				
Total port count	6	12	18	26
100/1000 Mbps	5	10	16	24
Gigabit SFP	1	2	-	-
Gigabit combo (RJ-45/SFP)	-	-	2	2
Configurable extended range ports	5	8	16	16
PoE				
PoE ports	5	8	16	24
Total PoE budget (watt)	60	130	250	375
PoE Standard	802.3af/at 802.3bt (port 1-2)	802.3af/at	802.3af/at	802.3af/at
Performance				
Switching capacity (Gbps)	12	24	36	52
Forwarding rate (Mpps)	8.9	17.8	26.7	38.7
Packet buffer (byte)	525 K	525 K	525 K	525 K
MAC address table	8 K	8 K	8 K	8 K
Power				
Input	52 V - 57 V DC	100 - 240 V AC, 50/60 Hz	100 - 240 V AC, 50/60 Hz	100 - 240 V AC, 50/60 Hz
Max. power consumption (watt)	72	160.3	300.9	448.9
Physical Specifications				
Dimensions	193 x 84 x 26 /	267 x 162 x 44 /	330 x 230 x 44 /	441 x 270 x 44 /

(WxDxH)(mm/in.)	7.6 x 3.31 x1.02	10.51x 6.38 x1.73	12.99 x 9.06 x1.73	17.36 x10.63 x 1.73
Weight (kg/lb.)	0.41/0.9	1.63/3.59	2.42/5.34	3.58/7.89
Included accessories	• Power adapter • Wall-mount kit	• Power cord • Rack mounting kit	• Power cord • Rack mounting kit	• Power cord • Rack mounting kit
ESD/Surge Protections				
Ethernet port surge protection	4 KV	4 KV	4 KV	4 KV
Power supply surge protection: 4 KV Line-GND		4 KV	4 KV	4 KV
Power supply surge protection: 2 KV Line-Line		2 KV	2 KV	2 KV
Ethernet port ESD protection (air/contact)	15 KV/8 KV	15 KV/8 KV	15 KV/8 KV	15 KV/8 KV
Environmental Specifications				
Operating	Temperature -20°C to 50°C/-4°F to 122°F Humidity 5% to 95% (non-condensing)	Temperature -20°C to 50°C/-4°F to 122°F Humidity 5% to 95% (non-condensing)	Temperature -20°C to 50°C/-4°F to 122°F Humidity 5% to 95% (non-condensing)	Temperature -20°C to 50°C/-4°F to 122°F Humidity 5% to 95% (non-condensing)
Storage	Temperature -40°C to 70°C/-40°F to 158°F Humidity 5% to 95% (non-condensing)	Temperature -40°C to 70°C/-40°F to 158°F Humidity 5% to 95% (non-condensing)	Temperature -40°C to 70°C/-40°F to 158°F Humidity 5% to 95% (non-condensing)	Temperature -40°C to 70°C/-40°F to 158°F Humidity 5% to 95% (non-condensing)
MTBF (hr)	2,021,885.87	1,065,025.45	1,699,692.18	888,495
Heat dissipation (BTU/hr)	245.52	546.62	1,026.07	1,530.75
Acoustic noise @ 25°C (dBA)	0 (Fanless)	27.3	39	40.1