

TP-Link TL-WPA4220 300Mb/s AC (220-240V) Wi-Fi  
powerline range extender KIT (3db)



RJ45: 2db, fehér  
Cikkszám: TL-WPA4220 TKIT  
Ár:  
**47 680 Ft**

|                          |                                                                                                                                  |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------|
| Garancia: 3 Év           |                                                                                                                                  |
| Plug Type                | EU                                                                                                                               |
| Standards and Protocols  | HomePlug AV, IEEE802.3, IEEE802.3u, IEEE802.11b/g/n                                                                              |
| Interface                | TL-WPA4220: 2× 10/100 Mbps Ethernet Port<br>TL-PA4010: 1× 10/100 Mbps Ethernet Port                                              |
| Button                   | Pair, Reset, Wi-Fi/Wi-Fi Clone<br>Maximum: 12.916W (220V/50Hz)                                                                   |
| Power Consumption        | Typical: 12.302W (220V/50Hz)<br>Standby: 8.780W (220V/50Hz)                                                                      |
| LED Indicator            | PWR, PLC, ETH, Wi-Fi/Wi-Fi Clone                                                                                                 |
| Dimensions ( W x D x H ) | TL-WPA4220: 2.1 x 1.6 x 3.7 in (54 x 40 x 94 mm)<br>TL-PA4010: 2.0 x 1.1 x 2.6 in (52 x 28.5 x 65 mm)                            |
| Range                    | 300 Meters over electrical circuit                                                                                               |
| WIRELESS FEATURES        |                                                                                                                                  |
| Frequency                | 2.4-2.4835GHz<br>11n: Up to 300Mbps(dynamic)                                                                                     |
| Signal Rate              | 11g: Up to 54Mbps(dynamic)<br>11b: Up to 11Mbps(dynamic)<br>270M: -68dBm@10% PER<br>130M: -68dBm@10% PER<br>108M: -68dBm@10% PER |
| Reception Sensitivity    | 54M: -68dBm@10% PER<br>11M: -85dBm@8% PER<br>6M: -88dBm@10% PER<br>1M: -90dBm@8% PER                                             |
| Wireless Security        | 64/128-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK                                                                                   |
| Advanced Functions       | Enable/DisableWireless Radio,WMM, Wireless Statistics                                                                            |
| Transmission Power       | CE:<20dBm(2.4GHz)<br>FCC:<30dBm                                                                                                  |
| SOFTWARE FEATURES        |                                                                                                                                  |
| Modulation Technology    | OFDM (PLC)<br>Powerline Security:<br>128-bit AES                                                                                 |
| Encryption               | Wireless Security:<br>WEP, WPA/WPA2, WPA-PSK/WPA2-PSK Encryption                                                                 |
| OTHERS                   |                                                                                                                                  |
| Certification            | CE, RoHS<br>? Powerline Ethernet Adapter 2× TL-WPA4220 & 1× TL-PA4010                                                            |
| Package Contents         | ? 3× 6.5 ft. (2 m) Ethernet cable (RJ45)                                                                                         |

**System Requirements** Windows 2000/XP/2003/Vista, Windows 7/8, Mac, Linux

Operating Temperature: 0°C~40°C (32°F ~104°F)

Storage Temperature: -40°C~70°C (-40°F ~158°F)

**Environment**

Operating Humidity: 10%~90% non-condensing

Storage Humidity: 5%~90% non-condensing