

TP-Link VIGI C330 Bullet smart home kültéri IP kamera IP67



3MP, 6mm F1.6 1/2.8" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, forgatható, 2304x1296, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, fehér, H.265+;H.264+

Cikkszám: VIGI C330 (6MM)

Ár:

36 970 Ft

KAMERA

Képzékelő
Optika

1/2.8" Progressive Scan CMOS

2.8 mm/ 4 mm/ 6 mm

2.8 mm: F1.6

Aperture

4 mm: F1.6

6 mm: F1.6

Lens Mount

M12

Látószög

2.8mm: 107.5°/57.2°/128.7°(H/V/D)

4mm: 89.1°/45.1°/106.9°(H/V/D)

6mm: 55.1°/30.2°/64°(H/V/D)

Day/Night Mechanism

IR Cut Filter

IR Working Distance

30m

Min. szükséges megvilágításColor: 0.005 Lux; 0 Lux with IR/White Light

Weatherproof Rating

IP67

Digital Noise Reduction

3D DNR

WDR

DWDR

HÁLÓZAT

Biztonság

Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication

Szabvány

TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS,
RTSP, NTP, UPnP UDP, SSL/TLS

API

ONVIF

Simultaneous Live View3 Main Streams & 3 Sub-Streams

Client

VIGI App, VIGI Security Manager, VIGI NVR, Web

ÁLTALÁNOS

Csomagolás tartalma

VIGI Network Camera
Quick Start Guide
Waterproof Cable Attachments
Mounting Accessories

Operating Temperature-30~60 °C

Certifications

CE/BSMI/VCCI/ONVIF

Méret (Ma x Sz x Mé)

174 × 78 × 70 mm

Material

Plastic

General Features

Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening

Power Supply

12V DC ± 5%, 5.5mm Coaxial Power Plug
PoE (802.3af/at, class 0)

Power Consumption

12V DC: Max 5.4W
PoE: Class 0

VIDEÓ/KÉP

Main Stream: H.265+/H.265/H.264+/H.264

Videó tömörítés	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264
Kép frissítés (frame) és felbontás	Main Stream: Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2304x1296, 2048x1280, 1920x1080, 1280x720 Sub-Stream: Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 704x576, 640x480, 352x288, 320x240
Max. Resolution	3MP (2304 × 1296)
Videótovábbítás	Main Stream Sub-Stream
Képbeállítás	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software, Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Video Bit Rate	64 Kbps to 4 Mbps
Day/Night Switch	Day/Night/Auto/Schedule
SMART FEATURE-SET	
Smart Event	Human & Vehicle Classification, Intrusion Detection, Line-Crossing Detection, Human Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (Illegal Login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region
FIZIKAI KEZELŐFELÜLET	
Hálózati csatlakozás	1 RJ45 10/100M Self-Adaptive Ethernet Port
Gomb	-
Video Output	-
On-board Storage	-
Built-in Microphone	Yes