

TP-Link VIGI C540-4G smart home kültéri IP kamera 4G/LTE IP66



4MP, 4mm F1.6 1/3" CMOS, Ethernet (100Mb/s), 4G/LTE, beépített mikrofon, beépített hangszóró, forgatható, 2560x1440, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, microSD, fehér-fekete, H.265+, 690g

Cikkszám: VIGI C540-4G (4MM)

Ár:

94 930 Ft

Garancia: 3 Év

KAMERA

Képérzékelő	1/3.06" Progressive Scan CMOS
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Min. szükséges megvilágítás	0.005 Lux; 0 Lux with IR/White Light
Day/Night Mechanism	IR Cut Filter
Day/Night Switch	Unified/ Scheduled/ Auto

LENS

Type	Fixed Focal Lens
Focal Length	4 mm
Aperture	F1.6
FOV	Horizontal FOV: 80°, Vertical FOV: 43°, Diagonal FOV: 94°
Lens Mount	M12*0.5
DORI Distance	Detect: 80 m (262 ft)
	Observe: 33 m (109 ft)
	Recognize: 16 m (52 ft)
	Identify: 8 m (26 ft)

PTZ

Pan/tilt Range	Pan: 0° to 348°, Tilt: 0° to 120° • Pan Speed: Configurable from 8° to 44°/s; Preset Speed: 44°/s
Pan/tilt Speed	• Tilt Speed: Configurable from 8° to 44°/s, Preset Speed 44°/s
Manual Control Speed	Configurable from 8° to 35°/s
Presets	300
Patrol Scan	8 patrols, up to 8 presets for each patrol
Power-off Memory	Yes; Auto restore to previous PT and lens status after power failure
Park Action	Yes; Preset; Patrol Scan
3D Positioning	Yes

ANGLE ADJUSTMENT (MANUAL)

Range	• Pan: 0° to 348° • Tilt: 0° to 120°
--------------	---

ILLUMINATOR

IR LED	• Quantity: 2 • Range: 30m
---------------	-------------------------------

	• Wavelength: 850nm • Quantity: 2 • Range: 30m
White LED	
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2560 X 1440 • Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Main Stream	• Resolution: 2560x1440, 2304x1296, 2048x1280, 1920x1080, 1280x720 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. • Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Sub-Stream	• Resolution: 640x480, 352x288, 320x240 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	• Main Stream: H.265+/H.265/H.264+/H.264 • Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile
H.265+	Main Stream Supported
Video Bit Rate	• Main Stream: 256 Kbps to 3 Mbps • Sub-Stream: 64 Kbps to 512 Kbps
IMAGE	
Image Settings	• Mirror • Brightness • Contrast • Saturation • Sharpness • Exposure, WDR, • White Balance • Prevent Overexposure to Infrared Light • HLC Adjustable by Client Software • Rotation (90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	DWDR
SNR	≥ 52 dB
Image Parameters Switch	Yes
Privacy Mask	Up to 4 Masks
ROI	1 Region
OSD Setting	Yes
HANG	
Hangkommunikáció	Two-Way Audio
Hangbemenet	Yes
Hangkimenet	Yes
Hangtömörítés	Yes
Audio Sampling Rate	8KHz
Environment Noise Filtering	Yes
Audio Bit Rate	64 Kbps(G.711 alaw)
HÁLÓZAT	
Szabvány	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF	Yes
API	ONVIF

Simultaneous Live View	2 Main Streams & 2 Sub-Streams
Client	VIGI App, VIGI Security Manager, Web UI • Google Chrome® 57 and above • Firefox® 52 and above • Safari® 11 and above • Microsoft® Edge 91 and above
Web Browser	
Cloud	Yes
Biztonság	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication
4G	
Standard	LTE-TDD/LTE-FDD/WCDMA
SIM Type	Nano SIM
Category	4 • LTE-FDD: B 1/3/5/7/8/20/28
Frequency	• LTE-TDD: B 38/40/41 • WCDMA: B 1/5/8

FIGYELMEZTETÉSI ÉS ESEMÉNYKEZELÉSI VEZÉRLÉS

	• Human & Vehicle Classification • Intrusion Detection • Line-Crossing Detection • Region Entering Detection • Region Exiting Detection • Object Abandoned Detection • Object Removal Detection • People Detection • Vehicle Detection • Motion Detection
Smart Event	
	• Video Tampering Detection • Exception (Illegal Login) • Memory Card Video Recording
Basic Event	
	• Message Push • Audible Warning • White Light Flashing
Alarm Linkage	
Linkage Method	N/A
Output Notification	Message Push

FIZIKAI KEZELŐFELÜLET

Hálózati csatlakozás	1 RJ45 10/100M Self-Adaptive Ethernet Port
Alarm	N/A
Reset Button	Yes
Power	DC Power Port
On-board Storage	Built-In Memory Card Slot, Support MicroSD Card, Up to 256 GB
Built-in Nano-SIM Card Slot	Yes
Built-in Microphone	Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker	Yes
Audio	N/A

ÁLTALÁNOS

Operating Temperature	-30~60 °C
Storage Temperature	-40~60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing) • VIGI Network Camera • Quick Start Guide • Waterproof Cable Attachments • Mounting Accessories • Power Adapter
Csomagolás tartalma	
Material	Plastic
Net Weight	0.69 Kg
Gross Weight	1.16 Kg
Power Supply	12V DC/1A, 5.5mm Coaxial Power Plug • Quantity: 2
	• Type: 690~960&1710~2690MHz Dipole Omni-Directional Antenna

Antenna	690~960&1710~2690MHz Dipole Omni-Directional Antenna
Protection	• Gain: Ant1:0.84dBi@690~960MHz, 2.85dBi@1710~2690MHz Ant2:0.74dBi@690~960MHz, 3.06dBi@1710~2690MHz IP66
Product Dimensions (L x W x H)	120 x 182 x 201 mm (excluding antennas)
Certifications	CE, RCM, BSMI, RoHS, NCC

4G/LTE	Van
alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	4MP
látószög	94°
smart home	Van
tömeg	690
videó felbontása	2560x1440
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP66
csatlakozó	Ethernet (100Mb/s)
döntési szög	120
éjszakai mód	Van
érzékelő típusa	4mm F1.6 1/3" CMOS
forgatási szög	348
forgatható	Van
kamera rögzítés típusa	falra és mennyezetre rögzíthető
memóriakártya foglalat	microSD
mozgásérzékelő	Van
rögzítési formátumok	H.265+
rögzítési sebesség	30
szín	fehér-fekete