

Huawei eKit Engine Gateway S380-L4T1T router

WAN (1Gb/s): 1 port, LAN (1Gb/s): 4 port, fehér

Cikkszám: 98012177

Ár:

72 150 Ft



Garancia: 3 Év	
First supported version	V600R022C10
Integrated fixed deviceY	
Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 35.0 mm x 210.0 mm x 130.0 mm (1.38 in. x 8.27 in. x 5.12 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 35.0 mm x 210.0 mm x 136.3 mm (1.38 in. x 8.27 in. x 5.37 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 285.0 mm x 180.0 mm (3.54 in. x 11.22 in. x 7.09 in.)
Chassis height [U]	0.8
Installation type	Desk mounting,Wall mounting
Weight without packaging [kg(lb)]	0.8 (1.76)
Weight with packaging [kg(lb)]	1.0 (2.2)
Typical power consumption [W]	5.99
Typical heat dissipation [BTU/hour]	27.3
Maximum power consumption [W]	6.11
Maximum heat dissipation [BTU/hour]	30.7
Static power consumption [W]	4.25
100% power consumption [W]	6.05
MTBF [year]	77.35
MTTR [hour]	2
Availability	>0.99999
Noise at normal temperature (acoustic Noise-free (no fans), < 30 power) [dB(A)]	
Noise at high temperature (acoustic Noise-free (no fans), < 30 power) [dB(A)]	
Noise at normal temperature (acoustic Noise-free (no fans), < 20	

pressure) [dB(A)]	
Number of card slots	0
Number of power slots	0
Number of fans modules	0
Maximum number of physical ports on the entire device	5
Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of 5GE ports	0
Maximum number of 2.5GE ports	0
Maximum number of GE ports	5
Maximum number of FE ports	5
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature [°C(°F)]	0°C to 40°C (32°F to 104°F) at an altitude of 0-1800 m (0-5906 ft.)
Restriction on the operating temperature variation rate [°C(°F)]	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH (non-condensing)
Long-term operating altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Power supply mode	Power adapter
Rated input voltage [V]	AC input: 100-240 V AC; 50/60 Hz
Input voltage range [V]	AC input: 90 V AC to 264 V AC; 45 Hz to 65 Hz Power adapter output: 12 V DC
Maximum input current [A]	1 A
CPU	Quad-core, 800 MHz
Memory	DDR4: 512 MB
Flash memory	NAND Flash: 512 MB
Storage	-
Console port	Not supported
Eth Management port	LAN port
USB	Not supported
Hardware real-time power detection	Not supported
Dying gasp	Not supported
RTC	Not supported
RPS input	Not supported
Complete device sleeping	Not supported
Service port surge protection [kV]	Common mode: ±4 kV

Power supply surge protection [kV]	Power adapter: ±6 kV in differential mode and ±6 kV in common mode		
Ingress protection level	IP20		
(dustproof/waterproof)			
Types of fans	None		
Heat dissipation mode	Natural heat dissipation		
Airflow direction	-		
PoE	Not supported		
Maximum PoE power consumption [W]	-		
PoE+ power interfaces	-		
PoE++ power interfaces	-		
Full load PoE power consumption 15.4W (802.3af)	-		
Full load PoE power consumption 30W (802.3at)	-		
Full load PoE++ power consumption 60W (802.3bt)	-		
Full load PoE++ power consumption 90W (802.3bt)	-		
Certification	EMC certification Safety certification Manufacturing certification		
LAN (1Gb/s)	4		
WAN (1Gb/s)	1		
Gyártó	Huawei		
szín	fehér		