

Huawei eKit Engine Gateway S380-S8P2T PoE router

WAN (1Gb/s): 2 port, LAN (1Gb/s): 8 port, fehér

Cikkszám: 98012180

Ár:

178 460 Ft



|   |  |
|---|--|
| Garancia: 3 Év  |  |
| First supported version   | V600R022C10  |
| Integrated fixed deviceY  |  |
| Dimensions without packaging (H x W x D) [mm(in.)]                              | Basic dimensions (excluding the parts protruding from the body): 35.0 mm x 210.0 mm x 130.0 mm (1.38 in. x 8.27 in. x 5.12 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 35.0 mm x 210.0 mm x 136.3 mm (1.38 in. x 8.27 in. x 5.37 in.) |
| Dimensions with packaging (H x W x D) [mm(in.)]                                 | 150.0 mm x 275.0 mm x 200.0 mm (5.91 in. x 10.83 in. x 7.87 in.)   |
| Chassis height [U]  | 0.8  |
| Installation type   | Desk mounting,Wall mounting  |
| Weight without packaging [kg(lb)]   | 1.5 (3.31)   |
| Weight with packaging [kg(lb)]  | 1.8 (3.97)   |
| Typical power consumption [W]   | 12.4   |
| Typical heat dissipation [BTU/hour]   | 42.3   |
| Maximum power consumption [W]   | 145.8 W (PoE: 124 W)   |
| Maximum heat dissipation [BTU/hour]   | 497.5  |
| Static power consumption [W]  | 7.53   |
| 100% power consumption [W]  | 12.52  |
| MTBF [year]   | 65.36  |
| MTTR [hour]   | 2  |
| Availability  | >0.99999   |
| Noise at normal temperature (acoustic Noise-free (no fans), < 30 power) [dB(A)] |  |
| Noise at high temperature (acoustic Noise-free (no fans), < 30 power) [dB(A)]   |  |
| Noise at normal temperature (acoustic Noise-free (no fans), < 20                |  |

|  |   |
|--|---|
| pressure) [dB(A)]  |   |
| Number of card slots   | 0   |
| Number of power slots  | 0   |
| Number of fans modules   | 0   |
| Maximum number of physical ports on the entire device            | 10  |
| Maximum number of 100GE ports                                    | 0   |
| Maximum number of 40GE ports                                     | 0   |
| Maximum number of 25GE ports                                     | 0   |
| Maximum number of 10GE ports                                     | 0   |
| Maximum number of 5GE ports                                      | 0   |
| Maximum number of 2.5GE ports                                    | 0   |
| Maximum number of GE ports                                       | 10  |
| Maximum number of FE ports                                       | 10  |
| Dedicated stack port   | Not supported   |
| Redundant power supply   | Not supported   |
| Long-term operating temperature [°C(°F)]                         | 0°C to 40°C (32°F to 104°F) at an altitude of 0-1800 m (0-5906 ft.)   |
| Restriction on the operating temperature variation rate [°C(°F)] | When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). |
| Storage temperature [°C(°F)]                                     | -40°C to +70°C (-40°F to +158°F)  |
| Long-term operating relative humidity [RH]                       | 5% RH to 95% RH (non-condensing)  |
| Long-term operating altitude [m(ft.)]                            | 0-5000 m (0-16404 ft.)  |
| Storage altitude [m(ft.)]  | 0-5000 m (0-16404 ft.)  |
| Power supply mode  | Power adapter   |
| Rated input voltage [V]  | Power adapter input: 100-240 V AC; 50/60 Hz Power adapter output: 56 V DC   |
| Input voltage range [V]  | Power adapter input: 90-290 V AC; 47-63 Hz  |
| Maximum input current [A]  | 2.68 A  |
| CPU  | Quad-core, 800 MHz  |
| Memory   | DDR4: 512 MB  |
| Flash memory   | NAND Flash: 512 MB  |
| Storage  | -   |
| Console port   | Not supported   |
| Eth Management port  | LAN port  |
| USB  | Not supported   |
| Hardware real-time power detection                               | Not supported   |
| Dying gasp   | Not supported   |
| RTC  | Not supported   |
| RPS input  | Not supported   |
| Complete device sleeping   | Not supported   |
| Service port surge protection [kV]                               | Common mode: ±4 kV  |

|   |  |  |  |
|---|--|--|--|
| Power supply surge protection [kV]              | Power adapter: ±6 kV in differential mode and ±6 kV in common mode |  |  |
| Ingress protection level (dustproof/waterproof) | IP20   |  |  |
| Types of fans                                   | None   |  |  |
| Heat dissipation mode                           | Natural heat dissipation   |  |  |
| Airflow direction                               | -  |  |  |
| PoE   | Supported  |  |  |
| Maximum PoE power consumption [W]               | 124 W  |  |  |
| PoE+ power interfaces                           | 8  |  |  |
| PoE++ power interfaces                          | -  |  |  |
| Full load PoE power consumption 15.4W (802.3af) | 8  |  |  |
| Full load PoE power consumption 30W (802.3at)   | 4  |  |  |
| Full load PoE++ power consumption 60W (802.3bt) | -  |  |  |
| Full load PoE++ power consumption 90W (802.3bt) | -  |  |  |
| Certification                                   | EMC certification Safety certification Manufacturing certification |  |  |
|   |  |  |  |
| LAN (1Gb/s)                                     | 8  |  |  |
| WAN (1Gb/s)                                     | 2  |  |  |
| Gyártó  | Huawei   |  |  |
| PoE   | Van  |  |  |
| szín  | fehér  |  |  |