

Huawei eKit Engine Wireless Access Point AP263 Dual-Band Wi-Fi PoE access point



2975Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 2 port, antennák száma: 2db, 4dBi, energiafelhasználás: 12W, fehér

Cikkszám: 50084981

Ár:

69 670 Ft

Garancia: 3 Év	
Integrated fixed device	Y
First supported version	V200R021C01
Installation Type	Desk,Wall,Ceiling,Junction Box
Dimensions without packaging (H x W x D) [mm(in.)]	160 mm x 86 mm x 38 mm (6.30 in. x 3.39 in. x 1.50 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	75 mm x 205 mm x 115 mm (2.95 in. x 8.07 in. x 4.53 in.)
Weight without packaging [kg(lb)]	0.320 kg (0.705 lb)
Weight with packaging [kg(lb)]	0.542 kg (1.195 lb)
CPU	2-core, 1.0 GHz
Memory	DDR3L: 512 MB
Storage	NAND Flash 256 MB
Console port	BLE console
Maximum power consumption [W]	12
Maximum heat dissipation [BTU/hour]	41
Power supply mode	DC adapter,PoE
Rated input voltage [V]	12 V
Input voltage range [V]	12±10% PoE: 802.3at/af
Service port surge protection [kV]	PoE port: Differential mode (48 V-RTN): 0.5 kV (1.2/50 us, 42 ohms), criterion B Common mode (8 wires to ground): 6 kV (1.2/50 us, 42 ohms), criterion B
Maximum number of physical ports on the entire device	GE (RJ45) x 2, 10M/100M/1000M auto-sensing
Long-term operating temperature [°C(°F)]	0°C to 40°C (32°F to 104°F) (If the altitude is in the range of 1800 m to 5000 m, the temperature decreases by 1°C or 1.8°F every time the altitude increases by 300 m.)
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH
Long-term operating altitude [m(ft.)]	-60 m to +5000 m (-196.85 ft to +16404.20 ft)
Atmospheric pressure [kPa]	53kPa - 106kPa ETSI 300 019-2-3
Ground	floating ground

USB	USB 2.0 (supporting 5 W power supply)
BLE	BLE5.0
Radio number	2
Operating frequency band	2.4GHz,5GHz
MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz): 2x2
Wi-Fi standard	2.4G: 802.11b/g/n/ax 5G: 802.11a/n/ac/ac Wave 2/ax
Radio interface	Built-in smart antennas
Antenna gain	2.4G: 2 dBi/chain (peak value) 1 dBi (combined gain) 5G: 3 dBi/chain (peak value) 1 dBi (combined gain) BLE: 4 dBi
Maximum transmit power	2.4G: 20 dBm/chain 23 dBm (combined power) 5G: 20 dBm/chain 23 dBm (combined power) BLE: < 10 dBm
3G/LTE filte (ACC)	Not supported
MTBF [year]	69.7
MTTR [hour]	0.5
Frequency stability [ppm]	+/-20
802.3at power supply description	No function is limited.
802.3af power supply description	The USB function is unavailable.
DC power supply description	No function is limited.

Dual-Band	Van
energiafelhasználás	12
LAN (1Gb/s)	2
PoE port	1
tömeg	320
Wi-Fi átviteli sebesség	2975
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)
Gyártó	Huawei
antenna nyeresége	4
antenna típusa	belső
antennák száma	2
PoE	Van
WI-FI	Van
szín	fehér