

Huawei eKit Engine Wireless Access Point AP361 Dual-Band Wi-Fi PoE access point

1775Mb/s, IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6), LAN (1Gb/s): 1 port, antennák száma: 2db, 3dBi, energiafelhasználás: 8,8W, fehér

Cikkszám: 50086871

Ár:

42 600 Ft



Garancia: 3 Év	
First supported version	V200R023C00
Integrated fixed device	Y
Installation Type	Wall,Ceiling,T-Rail
Dimensions without packaging (H x W x D) [mm(in.)]	Diameter x depth: 180 mm x 35 mm (7.09 in. x 1.38 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	200 mm x 231 mm x 61 mm (7.87 in. x 9.09 in. x 2.40 in.)
Weight without packaging [kg(lb)]	0.45 kg (0.99 lb)
Weight with packaging [kg(lb)]	0.75 kg (1.65 lb)
CPU	2-core, 1.2 GHz
Memory	DDR3 256 MB
Console port	None
Power supply mode	PoE
Storage	NAND Flash 256 MB
Rated input voltage [V]	NA
Input voltage range [V]	PoE: 802.3af
Service port surge protection	PoE port: Common mode (8 wires to ground): 4 kV (1.2/50 us, 42 ohms), criterion B Differential mode (48 V-RTN): 0.5 kV (1.2/50 us, 42 ohms), criterion B
Maximum number of physical ports on the entire device	GE (RJ45) x 1, 10M/100M/1000M auto-sensing
Long-term operating temperature [°C(°F)]	0°C to 40°C (32°F to 104°F) (From 1800 m to 5000 m [5905.51 ft. to 16404.20 ft.], the maximum temperature of the device decreases by 1°C [1.8°F] for every 300 m [984.25 ft.] increase in altitude.)
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH
Long-term operating altitude [m(ft.)]	-60 m to +5000 m (-196.85 ft to +16404.20 ft)
Atmospheric pressure [kPa]	53kPa - 106kPa ETSI 300 019-2-3
Ground	floating ground
Radio number	2

MIMO spatial streams	Radio 0 (2.4 GHz): 2x2 Radio 1 (5 GHz): 2x2
Wi-Fi standard	2.4G: 802.11b/g/n/ax 5G: 802.11a/n/ac/ac Wave 2/ax
Radio interface	Built-in smart antennas
Antenna gain	2.4G: 4 dBi/chain (peak) 2 dBi (combined gain) 5G: 5 dBi/chain (peak value) 3 dBi (combined gain)
Maximum transmit power	2.4G: 17 dBm/chain 20 dBm (combined power) 5G: 17 dBm/chain 20 dBm (combined power)
MTBF [year]	440.3
MTTR [hour]	2
Maximum power consumption [W]	8.8
Maximum heat dissipation [BTU/hour]	28.5
802.3bt power supply description	No function is limited.
802.3at power supply description	No function is limited.
802.3af power supply description	No function is limited.
DC power supply description	DC power supply is not supported.
Operating frequency band	2.4GHz,5GHz
Frequency stability [ppm]	+/-20

Dual-Band	Van
energiafelhasználás	8.8
LAN (1Gb/s)	1
PoE port	1
tömeg	450
Wi-Fi átviteli sebesség	1775
Wi-Fi jeltípus	IEEE 802.11a/b/g/n/ac/ax (Wi-Fi 6)
Gyártó	Huawei
antenna nyeresége	3
antenna típusa	belső
antennák száma	2
PoE	Van
WI-FI	Van
szín	fehér