

Huawei eKit Router AR720 rack router

WAN (1Gb/s): 2 port, LAN (1Gb/s): 8 port, USB2.0, fekete

Cikkszám: 02354GBG-001

Ár:

291 220 Ft

Garancia: 3 Év

Remarks	When configuring cards, ensure that the total power of the configured cards does not exceed 37 W or contact technical support engineers to obtain more suggestions.
Installation type	Rack,Work bench,Against the wall
Dimensions without packaging (H x W x D) [mm(in.)]	- Basic dimensions (excluding the parts protruding from the body): 44.4 mm x 442.0 mm x 220.4 mm (1.75 in. x 17.41 in. x 8.68 in.) - Maximum dimensions (the depth is the distance from ports on the front panel to the handle on the rear panel): 44.4 mm x 442.0 mm x 225.2 mm (1.75 in. x 17.41 in. x 8.87 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90 mm x 390 mm x 570 mm (3.54 in. x 15.35 in. x 22.44 in.)
Weight with packaging [kg(lb)]	4.6 (10.12)
Weight without packaging [kg(lb)]	3.2 (7.04)
CPU	1.4 GHz, 4 Cores
Memory	4 GB
Console port	RJ45
RTC	Supported
Maximum power consumption [W]	33
Power supply mode	AC built-in
Number of power modules	1
Rated input voltage [V]	100 V to 240 V, 50 Hz/60 Hz
Input voltage range [V]	90 V to 264 V, 47 Hz to 63 Hz
Maximum input current [A]	2
Maximum output power [W]	70
Safety regulation certification	IEC/EN/UL60950-1 IEC/EN/UL62368-1 GB 4943.1
EMC certification	EN 55032 EN 55035 CISPR 32 GB 9254 EN 55024 CISPR 24 GB/T 17618 EN 300 386 VCCI-CISPR 32 AS/NZS CISPR32 IEC 61000-3-2/EN 61000-3-2 IEC 61000-3-3/EN 61000-3-3

Type of fans	Built-in
Number of fan modules	0
Heat dissipation mode	Air cooling
Airflow direction	Left to right
Extended slots (standard configuration)	2 x SIC
Number of service board slots	2
Redundant power supply	Not supported
RPS input	Not supported
PoE	Not supported
Noise at normal temperature (acoustic power) [dB(A)]	52.3 dB(A)
Long-term operating temperature [°C(°F)]	0°C to 45°C (32°F to 113°F) Note: When the altitude is 1800 m-5000 m (5906 ft.-16404.2 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% to 95%, noncondensing
Long-term operating altitude [m(ft.)]	< 5000 m (16404.2 ft.)
MTBF [year]	30.05
MTTR [hour]	2
Availability	0.9999924012

Dual-personality Ethernet port	2
LAN (1Gb/s)	8
rack	Van
WAN (1Gb/s)	2
Gyártó	Huawei
USB2.0	2
szín	fekete