

Huawei eKit Switch S110-16LP2SR PoE rack switch

LAN (1Gb/s): 10 port, SFP: 2db, szürke
Cikkszám: 98012197
Ár:



103 030 Ft

Garancia: 3 Év	
Integrated fixed deviceY	
Dimensions without packaging (H x W x D)	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 260.0 mm (1.72 in. x 17.40 in. x 10.24 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 267.0 mm (1.72 in. x 17.40 in. x 10.51 in.)
Dimensions with packaging (H x W x D)	90.0 mm x 555.0 mm x 400.0 mm (3.54 in. x 21.85 in. x 15.75 in.)
Chassis height	1
Installation type	Rack mounting,Desk mounting,Wall mounting
Weight without packaging	3.0 (6.61)
Weight with packaging	3.7 (8.16)
Typical power consumption	22.0
Typical heat dissipation	75.07
Maximum power consumption	Without PoE: 22.0 W Full PoE load: 160.0 W (PoE: 124 W)
Maximum heat dissipation	Without PoE: 75.07 Full PoE load: 545.94
Static power consumption	12.0
100% power consumption	22.0
MTBF	57.77
MTTR	2
Availability	>0.99999
Noise at normal temperature (acoustic Noise-free (no fans), < 30 power)	
Noise at high temperature (acoustic Noise-free (no fans), < 30 power)	
Noise at normal temperature (acoustic Noise-free (no fans), < 20 pressure)	
Number of card slots	0
Number of power slots	0
Number of fans	

number of fans	0
modules	
Maximum number of physical ports on the entire device	18
Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of 5GE ports	0
Maximum number of 2.5GE ports	0
Maximum number of GE ports	18
Maximum number of FE ports	18
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature	0°C to 40°C (32°F to 104°F) at an altitude of 0-1800 m (0-5906 ft.)
Restriction on the operating temperature variation rate	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity	5% RH to 95% RH (non-condensing)
Long-term operating altitude	0-5000 m (0-16404 ft.)
Storage altitude	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage	AC input: 100-240 V AC; 50/60 Hz
Input voltage range	AC input: 90 V AC to 300 V AC; 47 Hz to 63 Hz
Maximum input current	3 A
CPU	-
Memory	-
Flash memory	-
Console port	Not supported
Eth Management port	Not supported
USB	Not supported
Hardware real-time power detection	Not supported
Dying gasp	Not supported
RTC	Not supported
RPS input	Not supported
Complete device sleeping	Not supported
Service port surge protection	Common mode: ±4 kV
Power supply surge protection	Differential mode: ±6 kV; common mode: ±6 kV
Ingress protection level	IP20
(dustproof/waterproof)	
Types of fans	None
Heat dissipation mode	Natural heat dissipation

Airflow direction	-
PoE	Supported
Maximum PoE power consumption	124
PoE+ power interfaces	16
PoE++ power interfaces	-
Full load PoE power consumption 15.4W (802.3af)	8
Full load PoE power consumption 30W (802.3at)	4
Full load PoE++ power consumption 60W (802.3bt)	-
Full load PoE++ power consumption 90W (802.3bt)	-
Certification	EMC certification Safety certification Manufacturing certification

LAN (1Gb/s)	10
rack	Van
SFP	2
Gyártó	Huawei
PoE	Van
szín	szürke