

Huawei eKit Switch S110-24LP2SR PoE rack switch

LAN (1Gb/s): 24 port, SFP: 2db, szürke

Cikkszám: 98012198

Ár:

149 540 Ft



Garancia: 3 Év

Integrated fixed deviceY

Dimensions without packaging (H x W x D) Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 260.0 mm (1.72 in. x 17.40 in. x 10.24 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 267.0 mm (1.72 in. x 17.40 in. x 10.51 in.)

Dimensions with packaging (H x W x D) 90.0 mm x 555.0 mm x 400.0 mm (3.54 in. x 21.85 in. x 15.75 in.)

Chassis height 1

Installation type Rack mounting,Desk mounting,Wall mounting

Weight without packaging 3.2 (7.05)

Weight with packaging 3.7 (8.16)

Typical power consumption 24

Typical heat dissipation 81.89

Maximum power consumption Without PoE: 24 W Full PoE load: 165 W (PoE: 124 W)

Maximum heat dissipation Without PoE: 81.89 Full PoE load: 563

Static power consumption 13

100% power consumption 24

MTBF 42.92

MTTR 2

Availability >0.99999

Noise at normal temperature (acoustic Noise-free (no fans), < 30 power)

Noise at high temperature (acoustic Noise-free (no fans), < 30 power)

Noise at normal temperature (acoustic Noise-free (no fans), < 20 pressure)

Number of card slots 0

Number of power slots 0

Number of fans

number of fans	0
modules	
Maximum number of physical ports on the entire device	26
Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of 5GE ports	0
Maximum number of 2.5GE ports	0
Maximum number of GE ports	26
Maximum number of FE ports	26
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature	0°C to 40°C (32°F to 104°F) at an altitude of 0-1800 m (0-5906 ft.)
Restriction on the operating temperature variation rate	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.).
Storage temperature	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity	5% RH to 95% RH (non-condensing)
Long-term operating altitude	0-5000 m (0-16404 ft.)
Storage altitude	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage	AC input: 100-240 V AC; 50/60 Hz
Input voltage range	AC input: 90 V AC to 300 V AC; 47 Hz to 63 Hz
Maximum input current	3 A
CPU	-
Memory	-
Flash memory	-
Console port	Not supported
Eth Management port	Not supported
USB	Not supported
Hardware real-time power detection	Not supported
Dying gasp	Not supported
RTC	Not supported
RPS input	Not supported
Complete device sleeping	Not supported
Service port surge protection	Common mode: ±4 kV
Power supply surge protection	Differential mode: ±6 kV; common mode: ±6 kV
Ingress protection level (dustproof/waterproof)	IP20
Types of fans	None
Heat dissipation mode	Natural heat dissipation

Airflow direction	-
PoE	Supported
Maximum PoE power consumption	124
PoE+ power interfaces	24
PoE++ power interfaces	-
Full load PoE power consumption 15.4W (802.3af)	8
Full load PoE power consumption 30W (802.3at)	4
Full load PoE++ power consumption 60W (802.3bt)	-
Full load PoE++ power consumption 90W (802.3bt)	-
Certification	EMC certification Safety certification Manufacturing certification

LAN (1Gb/s)	24
rack	Van
SFP	2
Gyártó	Huawei
PoE	Van
szín	szürke