

Huawei eKit Switch S220-24T4X rack switch

LAN (1Gb/s): 24 port, soros port, SFP+: 4db, szürke

Cikkszám: 98012375

Ár:

113 510 Ft



Garancia: 3 Év

S220-24T4X (24*10/100/1000BASE-T ports, 4*10GE SFP+ ports, built-in AC power)

Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.66 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)
Chassis height [U]	1
Installation type	Rack mounting,Desk mounting,Wall mounting
Chassis material	Metal
Weight without packaging [kg(lb)]	2.32 (5.11)
Weight with packaging [kg(lb)]	3.44 (7.58)
Typical power consumption [W]	27.27
Typical heat dissipation [BTU/hour]	93.05
Maximum power consumption [W]	35.04
Maximum heat dissipation [BTU/hour]	119.56
Static power consumption [W]	19.00
100% power consumption [W]	27.27
MTBF [year]	70.75
MTTR [hour]	2
Availability	> 0.99999
Noise at normal temperature (acoustic power) [dB(A)]	47
Noise at high temperature (acoustic power) [dB(A)]	51
Noise at normal temperature (acoustic power) [dB(A)]	35

pressure) [dB(A)]	
Number of fans modules	1
Maximum number of physical ports on the entire device	28
Maximum number of FE ports	24
Uplink ports	4 x 10GE SFP+ ports
Downlink ports	24 x 10/100/1000BASE-T ports
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature [°C(°F)]	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5905.44 ft.)
Restriction on the operating temperature variation rate [°C(°F)]	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). Devices cannot start when the temperature is lower than 0°C (32°F).
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH (non-condensing)
Long-term operating altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage [V]	AC input: 100-240 V AC; 50/60 Hz
Input voltage range [V]	AC input: 90 V AC to 264 V AC; 45 Hz to 65 Hz
Maximum input current [A]	0.8 A
CPU	1.1 GHz, 2 cores
Memory	2 GB
Flash memory	Physical space: 1 GB
Console port	RJ45
Power supply surge protection [kV]	Differential mode: ±6 kV; common mode: ±6 kV
Ingress protection level	IP20
(dustproof/waterproof)	
Types of fans	Built-in
Heat dissipation mode	Air cooling for heat dissipation, intelligent fan speed adjustment
Airflow direction	Air intake from left and front, air exhaustion from right
PoE	Not supported
Maximum number of 10GE ports	4
Maximum number of GE ports	28
Eth Management port	Not supported
USB	Not supported
Service port surge protection [kV]	Common mode: ±7 kV

LAN (1Gb/s)	24
rack	Van
SFP+	4
Gyártó	Huawei

soros port	1
szín	szürke