

Huawei eKit Switch S310-24T4S rack switch

LAN (1Gb/s): 24 port, soros port, SFP: 4db, szürke

Cikkszám: 98012202

Ár:

126 050 Ft



Garancia: 3 Év	
First supported version	V600R022C10
Integrated fixed deviceY	
Dimensions without packaging (H x W x D) [mm(in.)]	Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.66 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.)
Dimensions with packaging (H x W x D) [mm(in.)]	90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.)
Chassis height [U]	1
Installation type	Rack mounting,Desk mounting,Wall mounting
Weight without packaging [kg(lb)]	2.32 (5.11)
Weight with packaging [kg(lb)]	3.44 (7.58)
Typical power consumption [W]	26.37
Typical heat dissipation [BTU/hour]	89.98
Maximum power consumption [W]	34.04
Maximum heat dissipation [BTU/hour]	116.15
Static power consumption [W]	19.003
100% power consumption [W]	27.05
MTBF [year]	70.75
MTTR [hour]	2
Availability	>0.99999
Noise at normal temperature (acoustic power) [dB(A)]	47
Noise at high temperature (acoustic power) [dB(A)]	51
Noise at normal temperature (acoustic	35

pressure) [dB(A)]	
Number of card slots	0
Number of power slots	0
Number of fans modules	1
Maximum number of physical ports on the entire device	28
Maximum number of 100GE ports	0
Maximum number of 40GE ports	0
Maximum number of 25GE ports	0
Maximum number of 10GE ports	0
Maximum number of 5GE ports	0
Maximum number of 2.5GE ports	0
Maximum number of GE ports	28
Maximum number of FE ports	24
Dedicated stack port	Not supported
Redundant power supply	Not supported
Long-term operating temperature [°C(°F)]	-5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5905.44 ft.)
Restriction on the operating temperature variation rate [°C(°F)]	When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). Devices cannot start when the temperature is lower than 0°C (32°F).
Storage temperature [°C(°F)]	-40°C to +70°C (-40°F to +158°F)
Long-term operating relative humidity [RH]	5% RH to 95% RH (non-condensing)
Long-term operating altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Storage altitude [m(ft.)]	0-5000 m (0-16404 ft.)
Power supply mode	AC built-in
Rated input voltage [V]	AC input: 100-240 V AC; 50/60 Hz
Input voltage range [V]	AC input: 90-290 V AC; 45-65 Hz
Maximum input current [A]	0.8 A
CPU	1.1 GHz, 2 cores
Memory	2 GB
Flash memory	1 GB in total. To view the available flash memory size, run the display version command.
Console port	RJ45
Eth Management port	Not supported
USB	Not supported
Hardware real-time power detection	Not supported
Dying gasp	Supported
RTC	Not supported
RPS input	Not supported
Complete device sleeping	Not supported
Service port surge protection [kV]	Common mode: ±7 kV
Power supply surge	

Power supply surge protection [kV]	Differential mode: ±6 kV; common mode: ±6 kV
Ingress protection level	IP20
(dustproof/waterproof)	
Types of fans	Built-in
Heat dissipation mode	Air cooling for heat dissipation, intelligent fan speed adjustment
Airflow direction	Air intake from left and front, air exhaustion from right
PoE	Not supported
Maximum PoE power consumption [W]	-
PoE+ power interfaces	-
PoE++ power interfaces	-
Full load PoE power consumption 15.4W (802.3af)	-
Full load PoE power consumption 30W (802.3at)	-
Full load PoE++ power consumption 60W (802.3bt)	-
Full load PoE++ power consumption 90W (802.3bt)	-
Certification	EMC certification Safety certification Manufacturing certification

LAN (1Gb/s)	24
rack	Van
SFP	4
Gyártó	Huawei
soros port	1
szín	szürke