

Huawei eKit Switch S310-48P4X PoE rack switch

LAN (1Gb/s): 48 port, soros port, SFP+: 4db, szürke

Cikkszám: 98012385

Ár:

334 890 Ft



| | |
|--|--|
| Garancia: 3 Év | |
| First supported version | V600R023C00 |
| Integrated fixed deviceY | |
| Dimensions without packaging (H x W x D) [mm(in.)] | Basic dimensions (excluding the parts protruding from the body): 43.6 mm x 442.0 mm x 220.0 mm (1.72 in. x 17.4 in. x 8.66 in.) Maximum dimensions (the depth is the distance from ports on the front panel to the parts protruding from the rear panel): 43.6 mm x 442.0 mm x 227.0 mm (1.72 in. x 17.4 in. x 8.94 in.) |
| Dimensions with packaging (H x W x D) [mm(in.)] | 90.0 mm x 550.0 mm x 360.0 mm (3.54 in. x 21.65 in. x 14.17 in.) |
| Chassis height [U] | 1 |
| Installation type | Rack mounting,Desk mounting,Wall mounting |
| Chassis material | Metal |
| Weight without packaging [kg(lb)] | 3.24 (7.14) |
| Weight with packaging [kg(lb)] | 4.29 (9.46) |
| Typical power consumption [W] | 49.44 |
| Typical heat dissipation [BTU/hour] | 168.69 |
| Maximum power consumption [W] | - Without PoE: 64.7 W - Full PoE load: 462.80 W (PoE: 380 W) |
| Maximum heat dissipation [BTU/hour] | - Without PoE: 220.76 - Full PoE load: 1579.12 |
| Static power consumption [W] | 34.04 |
| 100% power consumption [W] | 49.44 |
| MTBF [year] | 48.14 |
| MTTR [hour] | 2 |
| Availability | > 0.99999 |
| Noise at normal temperature (acoustic power) [dB(A)] | 49.3 |
| Noise at high temperature (acoustic power) [dB(A)] | 63 |
| Noise at normal | |

| | |
|--|--|
| temperature (acoustic pressure) [dB(A)] | 37.3 |
| Number of card slots | 0 |
| Number of power slots | 0 |
| Number of fans modules | 2 |
| Maximum number of physical ports on the entire device | 52 |
| Maximum number of 100GE ports | 0 |
| Maximum number of 40GE ports | 0 |
| Maximum number of 25GE ports | 0 |
| Maximum number of 10GE ports | 4 |
| Maximum number of 5GE ports | 0 |
| Maximum number of 2.5GE ports | 0 |
| Maximum number of GE ports | 52 |
| Maximum number of FE ports | 48 |
| Uplink ports | 4 x 10GE SFP+ ports |
| Downlink ports | 48 x 10/100/1000BASE-T ports (380 W, PoE+) |
| Dedicated stack port | Not supported |
| Redundant power supply | Not supported |
| Long-term operating temperature [°C(°F)] | -5°C to +50°C (23°F to 122°F) at an altitude of 0-1800 m (0-5905.44 ft.) |
| Restriction on the operating temperature variation rate [°C(°F)] | When the altitude is 1800-5000 m (5906-16404 ft.), the highest operating temperature reduces by 1°C (1.8°F) every time the altitude increases by 220 m (722 ft.). Devices cannot start when the temperature is lower than 0°C (32°F). The operating temperature ranges from -5°C (23°F) to +45°C (113°F) when optical modules with transmission distances greater than or equal to 60 km are used. |
| Storage temperature [°C(°F)] | -40°C to +70°C (-40°F to +158°F) |
| Long-term operating relative humidity [RH] | 5% RH to 95% RH (non-condensing) |
| Long-term operating altitude [m(ft.)] | 0-5000 m (0-16404 ft.) |
| Storage altitude [m(ft.)] | 0-5000 m (0-16404 ft.) |
| Power supply mode | AC built-in |
| Rated input voltage [V] | - AC input: 100 V AC to 240 V AC, 50/60 Hz - High-voltage DC input: 240 V DC |
| Input voltage range [V] | - AC input: 90 V AC to 290 V AC; 45 Hz to 65 Hz - High-voltage DC input: 190 V DC to 290 V DC |
| Maximum input current [A] | 6 A |
| CPU | 1.1 GHz, 2 cores |
| Memory | 2 GB |
| Flash memory | Physical space: 1 GB |
| Console port | RJ45 |
| Eth Management port | Not supported |
| USB | Not supported |
| Hardware real-time power detection | Not supported |
| Dying gasp | Supported |
| RTC | Not supported |

| | |
|---|--|
| RPS input | Not supported |
| Complete device sleeping | Not supported |
| Service port surge protection [kV] | Common mode: ± 7 kV |
| Power supply surge protection [kV] | Differential mode: ± 6 kV; common mode: ± 6 kV |
| Ingress protection level (dustproof/waterproof) | IP20 |
| Types of fans | Built-in |
| Heat dissipation mode | Air cooling for heat dissipation, intelligent fan speed adjustment |
| Airflow direction | Air intake from left and air exhaust from right |
| PoE | Supported |
| Maximum PoE power consumption [W] | 380 |
| PoE+ power interfaces | 48 |
| Full load PoE power consumption 15.4W (802.3af) | 24 |
| Full load PoE power consumption 30W (802.3at) | 12 |
| Certification | EMC certification Safety certification Manufacturing certification |

| | |
|-------------|--------|
| LAN (1Gb/s) | 48 |
| rack | Van |
| SFP+ | 4 |
| Gyártó | Huawei |
| PoE | Van |
| soros port | 1 |
| szín | szürke |