

TP-Link EAP215-Bridge kültéri Wi-Fi PoE access point kit
(2db)



867Mb/s, IEEE 802.11ac (Wi-Fi 5), LAN (1Gb/s): 3 port, antennák száma:
2db, 11dBi, átviteli hatótávolság: 5000m, Mesh Wi-Fi, energiafelhasználás:
11,5W, fehér, IP65

Cikkszám: EAP215-BRIDGE KIT

Ár:

113 030 Ft

Garancia: 5 Év

HARDWARE FEATURES

Interface	3x Gigabit Ethernet Ports
Button	Reset
Power Supply	12V DC / 24V Passive PoE (Passive PoE adapter included.)
Dimensions (W x D x H)	8.8 x 3.1 x 2.4 in (224 x 79 x 60 mm)*4
Antenna Type	Internal 2x2 Dual-polarized directional MIMO antennas 5 GHz: 11.0 dBi
Weatherproof Enclosure	IP65
Mounting	Pole mounting (Accessories included)

WIRELESS FEATURES

Coverage	5000m(16400ft) ⁵
Wireless Standards	IEEE 802.11 a/b/g/n/ac/ax/be
Frequency	5 GHz
Signal Rate	5 GHz: Up to 867 Mbps • Mesh* ⁵ • MU-MIMO: 5G 2x2 MU-MIMO DL • Load Balance • Beamforming • Airtime Fairness

Wireless Functions

- Multiple SSIDs:8
- Wireless Statistics
- Wireless Schedule
- Reboot Schedule
- RADIUS Accounting
- MAC Authentication
- Static IP/Dynamic IP
- VLAN

Wireless Security

- Access Control
- Rogue AP Detection
- Captive Portal Authentication*⁵
- Maximum number of MAC Filter: 4,000
- Wireless Isolation between Clients
- WPA-Personal/Enterprise, WPA2-Personal/Enterprise, WPA3-Personal/Enterprise, OWE
- 802.1X Support
- CE:

Transmission Power

- <23dBm (5 GHz, band 1/2, EIRP);
- <30dBm (5 GHz band3, EIRP);

- FCC:
<22dBm (5 GHz band1/4)

MANAGEMENT

Omada App	Yes
Restore & Backup	Yes
Firmware update via Web	Yes
NTP	Yes

Centralized Management

Cloud Access

LED ON/OFF Control	Yes
Management MAC Access	Yes

SNMP	v1, v2c, v3
SSH	Yes
Web-based Management	Yes

OTHERS

Certification	CE, FCC, RoHS
	• EAP215-Bridge KIT • Passive PoE Adapter

Package Contents	• Power Cord • Installation Guide • Mounting Kit • Operating Temperature: -40 °C–70 °C (-40 °F–158 °F); • Storage Temperature: -40 °C–70 °C (-40 °F–158 °F); • Operating Humidity: 10%–90% non-condensing; • Storage Humidity: 5%–90% non-condensing
------------------	--

Environment

cikk kiegészítés	IP65
energiafelhasználás	11.5
LAN (1Gb/s)	3
Mesh Wi-Fi	Van
PoE port	1
Wi-Fi átviteli sebesség	867
Wi-Fi jeltípus	IEEE 802.11ac (Wi-Fi 5)
Wi-Fi titkosítás	WPA3;WPA3-Enterprise;WPA2-PSK;WPA2-Enterprise
Gyártó	TP-Link
antenna nyeresége	11
antenna típusa	belső
antennák száma	2
átviteli hatótávolság	5000
cikknév kiegészítés	(2db)
kit	Van
kültéri	Van

PoE	Van
WI-FI	Van
szín	fehér