

TP-Link VIGI C340I Bullet smart home kültéri IP kamera
(IP67)



4MP, 6mm F2.0 1/3" CMOS, Ethernet (100Mb/s), PoE, forgatható,
2560x1440, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, fehér,
H.265+

Cikkszám: VIGI C340I (6MM)

Ár:

32 850 Ft

CAMERA

Image Sensor	1/3" Progressive Scan CMOS
Lens	2.8 mm/ 4 mm/ 6 mm
	2.8 mm: F2.2
Aperture	4 mm: F2.2
	6 mm: F2.0
Lens Mount	M12
	2.8mm: 88.8°/48.9°/106.5°(H/V/D)
Viewing Angle	4mm: 75.1°/41.5°/88.7°(H/V/D)
	6mm: 47.7°/26.5°/56°(H/V/D)

Day/Night Mechanism IR Cut Filter

IR Working Distance 30m

Minimum Illumination Color: 0.1 Lux; 0 Lux with IR

Weatherproof Rating IP67

Digital Noise Reduction 3D DNR

WDR DWDR

NETWORK

Security Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication

Protocol TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS,
RTSP, NTP, UPnP UDP, SSL/TLS

API ONVIF

Simultaneous Live View 3 Main Streams & 3 Sub-Streams

Client VIGI App, VIGI Security Manager, VIGI NVR, Web

GENERAL

	VIGI Network Camera
	Quick Start Guide
Package Contents	Waterproof Cable Attachments
	Mounting Accessories

Operating Temperature -30-60 °C

Certifications CE/BSMI/VCCI/ONVIF

Dimensions(H X W X D)174 × 74 × 71 mm

Material Plastic

General Features Two Streams, Mirror, Privacy Masks, Password Reset via E-mail, HTTP Listening

Power Supply 12V DC ± 5%, 5.5mm Coaxial Power Plug
PoE (802.3af/at, class 0)

Power Consumption 12V DC: Max 5W
PoE: Class 0

VIDEO/IMAGE

Video Main Stream: H.265+/H.265/H.264+/H.264

Compression	Sub-Stream: H.265/H.264 Main Stream:
Frame Rate & Resolutions	Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 2560x1440,2304x1296, 2048x1280, 1920x1080, 1280x720 Sub-Stream: Frame Rate: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps Resolution: 640x480,352x288, 320x240
Max. Resolution	4MP (2560 × 1440)
Video Streaming	Main Stream Sub-Stream
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance Adjustable by Client Software, Rotation(90°/270°)
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Video Bit Rate	64 Kbps to 4 Mbps
Day/Night Switch	Day/Night/Auto/Schedule
SMART FEATURE-SET	
Smart Event	Human & Vehicle Classification, Intrusion Detection, Line-Crossing Detection, Human Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection
Basic Event	Motion Detection, Camera Tampering Detection, Exception (Illegal Login)
Linkage Method	Trigger Notification: ONVIF, HTTPS
Region of Interest	1 Region
INTERFACES	
Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port
Button	-
Video Output	-