

TP-Link VIGI C350 smart home kültéri IP kamera IP67



5MP, 6mm F1.6 1/2.7" CMOS, Ethernet (100Mb/s), PoE, beépített mikrofon, beépített hangszóró, forgatható, 2880x1620, 30fps, alakfelismerés, mozgásérzékelő, éjszakai mód, fehér, H.265+;H.264+

Cikkszám: VIGI C350 (6MM)

Ár:

41 080 Ft

Garancia: 3 Év

CAMERA

Image Sensor	1/2.7" Progressive Scan CMOS
Day/Night Switch	Unified/ Scheduled/ Auto
Shutter Speed	1/3 to 1/10000 s
Slow Shutter	Yes
Minimum Illumination	0.005 Lux; 0 Lux with IR/white light
Day/Night Mechanism	IR Cut Filter

NETWORK

Protocol	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
ONVIF	Yes
API	Open Network Video Interface (Profile S)
Simultaneous Live View	3 Main Streams & 3 Sub-Streams
Client	VIGI App, VIGI Security Manager Google Chrome® 57 and above Firefox® 52 and above Safari® 11 and above Microsoft® Edge 91 and above
Web Browser	
Cloud	Yes
Security	Password Protection, HTTPS Encryption, IP Address Filter, Digest Authentication

GENERAL

Operating Temperature	-30-60 °C
Storage Temperature	-40-60 °C
Operating Humidity	95% or Less (Non-Condensing)
Storage Humidity	95% or Less (Non-Condensing)
Package Contents	VIGI Network Camera Quick Start Guide Waterproof Cable Attachments Mounting Accessories
Material	Plastic
Power Supply	12V DC ± 5%, Max. 9 W, 5.5 mm Coaxial Power Plug PoE: 802.3af/at, class 0, Max. 10.5 W
Protection	IP67
Product Dimensions (L x W x H)	78.42× 186.88× 71.55 mm
Certifications	CE, NTRA, VCCI, KC, BSMI, FCC, IC

INTERFACES

Network Interface	1 RJ45 10/100M Self-Adaptive Ethernet Port, PoE
Alarm	N/A
Reset Button	Yes
Power	DC Power Port

On-board Storage Built-In Memory Card Slot, Support MicroSD Card, up to 256 GB
Built-in Microphone Yes; Records Anything Going on within a 15-ft Radius of the Camera
Built-in Speaker Yes
Audio N/A

ALARM AND EVENT MANAGEMENT

Smart Event Human & Vehicle Classification, Area Intrusion Detection, Line-Crossing Detection, People Detection, Vehicle Detection, Region Entering Detection, Region Exiting Detection, Object Abandoned Detection, Object Removal Detection, Loitering Detection, Scene Change Detection
Basic Event Motion Detection, Video Tampering Detection, Exception (Illegal Login), Scene Change Detection
Alarm Linkage Memory Card Video Recording, Message Push, Audible Warning, White Light Flashing
Linkage Method N/A
Output Notification Message Push

DEEP LEARNING FUNCTION

People & Vehicle Analytics Search and filter to people or vehicle of interest based on many different attributes, making post-event search faster and easier.
Multi-Target-Type Detection Supports Simultaneous Detection and Capture of Human Body and Vehicle
Face Capture N/A
Face Comparison N/A

LENS

Type Fixed Focal Lens
Focal Length 4 mm
Aperture F1.6
2.8mm:
Horizontal FOV: 109°, Vertical FOV: 57°, Diagonal FOV: 128°

FOV 4mm:
Horizontal FOV: 90°, Vertical FOV: 48°, Diagonal FOV: 107°

Lens Mount 6mm:
Horizontal FOV: 56°, Vertical FOV: 30.5°, Diagonal FOV: 66°
M12*P 0.5
2.8 mm
Detect: 63 m (206 ft)
Observe: 85 m (109 ft)
Recognize: 12 m (39 ft)
Identify: 6 m (19 ft)

DORI Distance 4 mm
Detect: 80 m (262 ft)
Observe: 33 m (109 ft)
Recognize: 16 m (52 ft)
Identify: 8 m (26 ft)

6 mm
Detect: 120 m (393 ft)
Observe: 50 m (164 ft)
Recognize: 24 m (78 ft)
Identify: 12 m (39 ft)

ANGLE ADJUSTMENT (MANUAL)

Range Pan: 0° to 360°, Tilt: 0° to 90°, Rotation: 0° to 360°

AUDIO

Audio Communication Two-Way Audio
Audio Input Yes
Audio Output Yes
Audio Compression Yes
Audio Sampling Rate 8KHz
Environment Noise Filtering Yes

Audio Bit Rate	64 Kbps(G.711 alaw)
ILLUMINATOR	
IR LED	Quantity: 2 Range: 30m Wavelength: 850nm
White LED	Quantity: 2 Range: 30m
Illuminator On/Off Control	Auto/Scheduled/Always on/Always off
VIDEO	
Max. Resolution	2880 X 1620 Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Main Stream	Resolution: 2880x1620,2688x1520, 2304x1296, 2048x1280, 1920x1080,1280x720 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps. Frame Rate: 50Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps 60Hz: 1fps, 5fps, 10fps, 15fps, 20fps, 25fps, 30fps
Sub-Stream	Resolution: 704x576,640x480, 352x288, 320x240 Note: If the image rotation is set to 90° or 270°, the frame rate only supports up to 20fps.
Bit Rate Control	CBR, VBR
Video Compression	Main Stream: H.265+/H.265/H.264+/H.264 Sub-Stream: H.265/H.264
H.264 Type	Main Profile/High Profile
H.264+	Main Stream Supported
H.265 Type	Main Profile?
H.265+	Main Stream Supported?
Video Bit Rate	Main Stream: 256 Kbps to 6 Mbps Sub-Stream: 64 Kbps to 512 Kbps
IMAGE	
Image Settings	Mirror, Brightness, Contrast, Saturation, Sharpness, Exposure, WDR, White Balance, Prevent Overexposure to Infrared Light, HLC Adjustable by Client Software
Image Enhancement	BLC/3D DNR/HLC/SmartIR
Wide Dynamic Range	120 dB Note: When People & Vehicle Analytics is enabled, only DWDR is supported.
SNR	? 52 dB
Image Parameters Switch	Yes
Privacy Mask ROI	Up to 4 Masks 1 Region
OSD Setting	Yes

alakfelismerés	Van
beépített hangszóró	mono
érzékelő felbontása	5MP
látószög	66°
smart home	Van

videó felbontása	2880x1620
Gyártó	TP-Link
beépített mikrofon	Van
cikknév kiegészítés	IP67
csatlakozó	Ethernet (100Mb/s)
döntési szög	90
éjszakai mód	Van
érzékelő típusa	6mm F1.6 1/2.7" CMOS
forgatási szög	360
forgatható	Van
kamera rögzítés típusa	falra rögzíthető
mozgásérzékelő	Van
PoE	Van
rögzítési formátumok	H.265+;H.264+
rögzítési sebesség	30
szín	fehér